

FAT TRUCK® 2.8 CARGO - ARCTIC

 FATTTRUCK®
DEFENSE

Ruf Diamond LTD.

62 Smelter Road

Coniston, ON, Canada, P0M 1M0

705-419-2653

info@rufdiamond.com

www.rufdiamond.com

FAT TRUCK® 2.8 CARGO - ARCTIC

SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		STORAGE & GEAR	
Payload	2200 lb (1000 kg)	Make	Hatz	Front & Rear	FAT TRUCK® LGP 1640 x 640 x 610	Heavy duty airline-style L-track	
Passengers capacity	2 (2 front + 0 rear)	Model	1.95 L Turbo diesel NO DEF	Pressure	0.5 to 4.5 PSI (0.07 to 0.31BAR)	Overhead and sides net storage	
Maximum speed on land	25 mph (40 km/h)	Emission standards	EPA Tier 4 Final or EDG (JP-8 fuel)	Pressure control	Automatic pressure control	Roof rack with ladder	
Maximum speed on water	3.1 mph (5 km/h)	Number of cylinders	4 cylinders	Wheel pods™			
Maximum uphill & downhill	35°/ 70%	Displacement	119 po³ (1.95 L)	FUEL SYSTEM			
Maximum sidehill	22°/ 40%	Horsepower @ 2300 RPM	74 hp (55 kW) or 83 hp (61 kW)	Capacity	21 US Gal (80 L)	4 x corner led beacon lights	
Turning radius	0°	Cooling System	Liquid cooled	Average fuel autonomy	12 h	360° camera with recorder	
Shipping weight	6000 lb (2722 kg)	ELECTRICAL		TOW PACKAGE & RECOVERY		360° LED bar lighting	
Ground pressure fully loaded	1.6 lb/in² (0.11 kg/cm²)	Voltage	12 V or 24 V	Front bumper w/ integrated winch		Directional light with remote control	
SAFETY FEATURES		Alternator capacity	275 A or 160 A	Rear hitch receiver with harness		Roof hatch	
ROPS	ISO 3471	Battery capacity	960 CCA	Chassis built-in anchors w/ redundancy		VISIBILITY	
Brakes	Automatic safety brake	Battery type	AGM	Rear winch connectors		4 x corner led beacon lights	
Electronic inclinometer with alarm		TRANSMISSION		High speed towing package		360° camera with recorder	
Backup alarm		Type	Hydrostatic	MISSION READY		360° LED bar lighting	
Backup alarm		BRAKES		Blackout mode		Directional light with remote control	
Height	111 in (2819 mm)	Brakes	Positive deceleration through hydrostatic transmission	Mechanical compass		Roof hatch	
Length	146.5 in (3720 mm)	Parking brakes	Brake disc applied pressure released	Additional battery		SAFETY FEATURES	
Width	100 in (2540 mm)	CONTROLS		Rear door stopper		Heavy duty airline-style L-track	
Ground clearance	20.7 in (526 mm)	Controller	Microprocessor	Communication ready package		Overhead and sides net storage	
CONTROLS		Steering	Joystick	Easy access battery lugs		Roof rack with ladder	
Display	Color display	WARRANTY		Keyless doors & fuel cap		FAT TRUCK DEFENSE	
WARRANTY		WARRANTY		Bilge pump switch		FAT TRUCK DEFENSE	

Limited 1 year / 1000 hours
(Whichever comes first)

