

FT3 PICKUP



FATXTRUCK®
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



WE'LL GET YOU THERE™



62 Smelter Road
Coniston, Ontario, P0M 1M0

705-419-2653 | info@rufdiamond.com
www.rufdiamond.com

FT3 PICKUP



SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload on land	3000 lb (1357 kg)	Make	HATZ	Front & Rear	FAT TRUCK® 1640 x 640 x 610	Custom color	
Payload on water	2200 lb (998 kg)	Model	4H50TICD	Pressure	0.5 to 4.5 PSI (0.07 to 0.31 BAR)	Front LED light bar	
Passenger capacity	8 (2 front + 6 rear)	Emission standards	EPA Tier 4 Final EURO Stage V	Pressure control	Automatic pressure control	Rear LED light bar	
Maximum speed on land	25 mph (40 km/h)	Number of cylinders	4 cylinders	FUEL SYSTEM		Side working LED lights front and rear	
Maximum speed on water	3.1 mph (5 km/h)	Displacement	1.95 L	Average fuel	22 US Gal (83 L)	Search light	
Maximum uphill & downhill	35° / 70%	Horsepower	74 hp (55 kW)	autonomy	12 h	Air conditioning	
Maximum sidehill	22° / 40%	Torque @ 1400 RPM	177 lb-ft (240 N-m)	STANDARD EQUIPMENT		Front feet heater	
Turning radius	0°	Cooling system	Liquid cooled	Standard color: Red or white			
Base weight	6500 lb (2941 kg)	ELECTRICAL		Lockable door			
Ground pressure fully loaded	1.6 lb/in ² (0.11 kg/cm ²)	Voltage	12 V	2 front seats with 3-points seat belts			
SAFETY FEATURES		Alternator capacity	370 A	2 openable side windows			
ROPS	ISO 3471	Battery capacity	960 CCA	Ventilation fan			
EPA	Stage V	Battery type	AGM	Lights: Front, brakes, position, flashers, dome			
Brakes	Automatic safety brake	TRANSMISSION		4 corner LED beacon amber lights			
DIMENSIONS		Type	Hydrostatic	Backup alarm			
Height with roof rack	103 in (2620 mm)	Final drive	4 Hydraulic motors	Front mirrors			
Height with air conditioning	111.4 in (2830 mm)	BRAKES		Front and rear bumpers with hitch			
Length	147 in (3730 mm)	Brakes	Positive deceleration through hydrostatic transmission	Front and rear ladder with grab handles			
Width	100 in (2540 mm)	Parking brakes	Brake disc applied pressure released	Front roof rack			
Ground clearance	25.5 in (650 mm)	CONTROLS		Electric horn			
WARRANTY		Controller	Microprocessor	Inclinometer with alarm			
Limited 1 year / 1000 hours (Whichever comes first)		Steering	Joystick	Backup camera or 4-way backup camera			
		Display	Color display	Master cut-off switch			
				Cup holders			
				2 x 12 V charging ports			
				Lockable fuel cap			
				Bilge pump			
				Wheel Pods™			
				Fire extinguisher 2.5 lb ABC			
				First aid kit			
				Operator & Maintenance manual			
				Radio Bluetooth®			

