

FT3 WAGON



FAT X TRUCK®
INDUSTRIAL OFF-ROAD UTILITY VEHICLES



WE'LL GET YOU THERE™



62 Smelter Road
Coniston, Ontario, P0M 1M0

705-419-2653 | info@rufdiamond.com
www.rufdiamond.com

FT3 WAGON



SPECIFICATIONS

PERFORMANCE		ENGINE		TIRES		OPTIONS	
Payload on land	3000 lb (1357 kg)	Make	HATZ	Front & Rear	FAT TRUCK® 1640 x 640 x 610	Custom color	
Payload on water	2200 lb (998 kg)	Model	4H50TICD	Pressure	0.5 to 4.5 PSI (0.07 to 0.31 BAR)	Front LED light bar	
Passenger capacity	8 (2 front + 6 rear)	Emission standards	EPA Tier 4 Final EURO Stage V	Pressure control	Automatic pressure control	Rear LED light bar	
Maximum speed on land	25 mph (40 km/h)	Number of cylinders	4 cylinders	FUEL SYSTEM		Side working LED lights front and rear	
Maximum speed on water	3.1 mph (5 km/h)	Displacement	1.95 L	Capacity	22 US Gal (83 L)	Search light	
Maximum uphill & downhill	35° / 70%	Horsepower	74 hp (55 kW)	Average fuel autonomy	12 h	Air conditioning	
Maximum sidehill	22° / 40%	Torque @ 1400 RPM	177 lb-ft (240 N-m)	STANDARD EQUIPMENT		Ventilation fans	
Turning radius	0°	Cooling system	Liquid cooled	Standard color: Red or white		35 000 BTU cab heater	
Base weight	6900 lb (3122 kg)	ELECTRICAL		Lockable doors		Front feet heater	
Ground pressure fully loaded	1.6 lb/in ² (0.11 kg/cm ²)	Voltage	12 V	2 front seats with 3-points seat belts		Fuel cab heater	
SAFETY FEATURES		Alternator capacity	370 A	4 sliding side windows with bug screen		Fuel heater for engine water and transmission oil	
ROPS	ISO 3471	Battery capacity	960 CCA	Lights: Front, brakes, position, flashers, dome		110 V heater cold engine water and transmission oil	
EPA	Stage V	Battery type	AGM	4 corner LED beacon amber lights		Rear seats with 2 pts safety belts	
Brakes	Automatic safety brake	TRANSMISSION		Backup alarm		Rear seats with 3 pts safety belts	
DIMENSIONS		Type	Hydrostatic	Front mirrors		4-forward facing seats	
Height with roof rack	109 in (2763 mm)	Final drive	4 Hydraulic motors	Front and rear bumpers with hitch		Additional battery	
Height with air conditioning	115.2 in (2927 mm)	BRAKES		Front and rear ladder with grab handles		Front, rear winch	
Length	147 in (3730 mm)	Brakes	Positive deceleration through hydrostatic transmission	Rear roof rack with side ladder		Rear capstan winch	
Width	100 in (2540 mm)	Parking brakes	Brake disc applied pressure released	Electric horn		Studs for ice	
Ground clearance	25.5 in (650 mm)	CONTROLS		Inclinometer with alarm		Hot sticks storage tubes	
Controller		Microprocessor		Backup camera or 4-way backup camera		Ladder rack	
Steering		Joystick		Master cut-off switch		Storage box	
Display		Color display		Cup holders		Pintle hook	
WARRENTY		Limited 1 year / 1000 hours (Whichever comes first)		3 x 12 V charging ports		Radio Bluetooth®	
				Lockable fuel cap			
				Bilge pump			
				Wheel Pods™			
				Fire extinguisher 2.5 lb ABC			
				First aid kit			
				Operator & Maintenance manual			

