Hardwood

The depth of choice offered by one of the most used materials in the world, has seen different varieties of hardwood trees used for everything from the Ark to modern architecture. Now there's a better way, and for naturally good-looking floors without the noise, cost or maintenance of real wood, each of these designs will add different degrees of warmth and texture to your home.

Extended Specifications

Heavy Commercial Use Classification: Rigid Board Click Type of Installation:

Overall Thickness: 6mm Wear Layer Thickness: 0.55mm

Plank Size: 1517.6mm x 234.9mm (l x w)

SQM Per Box: 2.14sqm

Quantity of Planks Per Box: 6 **VOC Tested:** Passed

Global GreenTag Certification: Number of planks: 6 planks per box

Quantity per box: 2.14m2 Micro Scratch Resistance: Effect of Furniture Leg: Fire Index: Slip Resistance: Residual Indentation: Electrostatic Behaviour:

Dimensional Stability: Sound Absorption: Castor Chair:

Passed (EN16094) Passed (EN424) Bfl-s1 (EN13501) Passed (EN13893) Passed (EN 24343) Antistatic (EN 1815) Passed (EN 23999) Passed (ASTM 492-09) Passed (EN 425) (Use soft non-staining wheels)



B



Hardwood



Heating





Commercial





















Bill of Quantities

- Belgotex Hardwood 6mm heavy commercial right board click LVT.
- · 1517.6mm x 234.9mm (l x w) with 0.55 mm wear layer.
- 20-year residential warranty and 10-year commercial warranty.
- · This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- Green tag level A Gold rated certification.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.