

# B.

## Standard Plus

### More from your floor

Flooring affects performance in healthcare, education, housing, and commercial spaces. Standard Plus homogeneous vinyl sheeting boosts efficiency in high traffic or specialised areas with aesthetic appeal and intensive functionality. Engineered in Sweden in 30 versatile colours with soft linear patterns and a PUR surface finish for enhanced durability and easy maintenance. Featuring ISO 10581 conformity, 25% recycled content and 100% recyclable. The responsible choice for specifiers, contractors and developers looking to make a positive impact on their project, and beyond.

### Extended Specifications

Use Classification: (EN1307)	Heavy Commercial
Type of Installation:	Fully Flexible Directional Vinyl Sheeting
Total Weight: (ISO 23997)	3300 g/m <sup>2</sup>   97.32 oz/yd <sup>2</sup>
Top Layer Thickness: (ISO 24340)	2.0 mm   0.07 in
Total Thickness: (ISO 24346)	2.0 mm   0.07 in
Roll Size (l x w):	23 x 2 m   905.51 x 78.74 in
Top Layer:	Polyurethane Reinforced Coating
Backing Type:	Homogenous Vinyl Floor Covering
Chemical Resistance: (EN ISO 26987)	Yes
Fire Classification: (EN 13501-1)	Bfl-s1



An exclusive partnership with 

**Belgotex™**



# B.

## Standard Plus

More from your floor

### Extended Specifications

Slip Resistance: (DIN 51130)	R9
Residual Indentation: (EN ISO 24343-1)	<0.10mm
Thermal Conductivity: (EN 12667)	0.01m <sup>2</sup> K/W
Electrostatic Propensity: (Body Voltage Test) (EN 1815 Method A)	≤2.0kV
Dimensional Stability: (EN ISO 23999)	≤0.40% for rolls
Colour Fastness: (ISO 105-B02)	≥6
Seam Strength: (EN 684)	Individual values ≥ 180N/50mm
Castor Chair Suitability: (EN ISO 4918)	Suitable
Floor Heating System	Yes, max 27°C
VOC Emissions: (ISO 16000-9)	≤10 µg/m <sup>3</sup> (after 28 days)
Bacterial Resistance: (ISO 26987)	Does not favour growth
Warranty:	20 years
Sustainability:	Floorscore





# B.



Dark Green 921



Grey 498



Light Beige 479




Medium Blue 493



Stone Grey 924

# Standard Plus

More from your floor



## Bill of Quantities

- Belgotex STANDARD PLUS 2.0mm Homogenous Heavy Commercial Fully Flexible Directional Vinyl Sheeting.
- Available in 23 x 2m rolls with 2.0mm top layer.
- 20-year commercial warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- Green tag level A Gold rated certification.

\*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.