B

Affect

Affect is a dynamic, tufted carpet range, designed to elevate interior spaces by engaging positive emotions, perceptions, and overall well-being. Engineered from our bespoke polypropylene yarn, it offers durability and practicality to meet the demands of office environments. The organic patterns harmonise with any aesthetic yet also allow for out-of-the-box creativity when it comes to designing distinctive floorscapes. Affect presents a modern palette of 9 neutral and versatile colours that exude tranquillity and rejuvenation, fostering productive work environments that inspire!

Extended Specifications

Use Classification: (EN 1307)

Construction:

Product Description:

Yarn Type:

Yarn Mass: (ISO 8543) Pile Height: (ISO 8543)

Total Thickness: (ISO 8543)

Total Mass: (ISO 8543)

MTO Sizes (tile):

MTO Backing Options:

Medium / General Commercial

Tufted Multi Scroll Loop Pile

Tufted Loop Pile Bitumen Tile

Stainproof Miracle Fibre – Polypropylene

±520 (g/m²) (±15) | ±15.33 (oz/yd²) (±0.44)

±5 (mm) (±0.5) | ±0.19 (in) (±0.02)


±7.0 (mm) (±0.5) | 0.27 (in) (±0.02)

±4045 (g/m²) ** (±5%) | ±119.30 (oz/yd²) ** (±5%)

50×50cm / 100 X 25cm | 19.69×19.69(in) / 39.37 × 9.84 (in)

NexBac (NB)





Extended Specifications

Machine Gauge: 1/10"

Stitch Rate: 36 stitches/10cm | 36 stitches/3.94(in)

Fire Classification: (EN1305) (SANS10177-4)

Bfl-s1 / Rating 3

Colour Fastness to light: (NF EN ISO 105-BO2) > 6.0

Colour Fastness to Rubbing (staining): (ISO 105-X12) 4-5

Colour Fastness to Water (staining): (ISO 105-EO1) 4-5

Electrostatic Propensity: Body voltage: (ISO 6356: 2012) ≤ 2.0 kV

Sound Absorption (NexBac NB): (ISO 354: 2023) aw: 0.15
Sound Insulation (NexBac NB): (ISO 10140-3: 2021) 25 dB

Thermal Resistance: (ISO 8302: 2001) 0.0740 m².KW

Dimensional Stability: (ISO 986: 2006) ≤ 0.2% VOC Emissions (GBCSA/ GBCA & CRI Specifications): (ASTM D5116: 2017) Passed

Castor Chair Suitability: (NF EN 985 – Method A)

Occasional Use

Warranty: 15 years
Guarantee: 5 years



^{**} Weighted Average

B

Breathless Brightly Daybreak Growth Renew Revival Shadow Sprig

Affect



















Medium/General Commercial

From Local & Imported Goods





















Bill of Quantities

- · Belgotex AFFECT 50×50cm / 100×25cm) Medium/General Commercial 7.0mm width Nexbac tiles are manufactured from Stainproof Miracle Fibre (Polypropylene).
- · This product is to be laid in accordance with the SANS 10186 fitting code of practice.
- Belgotex AFFECT tiles to be installed in the following directions: Ashlar / Random Ashlar / Brick / Monolithic / Herringbone (planks) / Tessellated.
- · Belgotex recommends the use of Carpet protector mats where castor wheels are used.
- 15-year warranty and 5-year guarantee.
- Made in South Africa.
- · Green tag level A Gold rated certification.

Product characteristics may vary due to the nature of manufacturing. To combat colour variance do not install more than one dye lot in a single colour tile/plank installation. Where different dye lots and products are mixed and matched then size variations could take place and tiles might need to be altered during installation. When installing two or more different colours in tiles/planks/shapes then there is no issue mixing dye lots together. Sample swatches have been cut from an overall design; therefore, the decoration and shades may vary. A difference in appearance from the pattern is likely, as the product is not intended to have a uniform appearance.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.

Sway