

B.

Apex

The optimal mix of convenience, durability, and performance of heterogeneous vinyl. This range is designed specifically for heavy traffic areas, like commercial offices, retail, general industrial, and even frail care units. Manufactured in solid 4m wide sheets, fewer seams mean no shrinkage or expansion, with the added benefit of being able to handle liquid spills. Available in eight warm and cool tones across comforting timber and desirable terrazzo patterns, Apex is the ultimate heterogeneous vinyl to suit any design. Featuring a useful 0.6mm wear layer and a 10-year warranty, the Apex range is your key to long-term value through durability and performance.

Extended Specifications

Type of Installation:	Heterogeneous Vinyl Sheeting
Use Classification:	Heavy Commercial
Total Mass:	2200 (g/m ²) 70.95 (oz/yd ²)
Wear Layer Thickness:	0.60 (mm) 0.023 (in)
Total Thickness:	2.40 (mm) 0.094 (in)
Product Width:	4.00 (m) 157.48 (in)
Roll Length (LM):	27
Backing Type:	Powerbac
C hemical Resistance:	Yes (EN ISO 26987)



B.

Apex

Extended Specifications

Fire Classification:	Bfl-s1 (EN 13501-1)
Slip Resistance:	R10 (DIN 51130)
Residual Indentation:	≤0.15mm (EN ISO 24343-1)
Thermal Resistance:	0.016(m²*K)/W (EN 12664)
Electrostatic Propensity: (Body Voltage Test)	<2kV (on concrete) (EN 1815 Method A)
Dimensional Stability:	≤0.40% (EN ISO 23999)
Sound Absorption:	Δ Lw 16 dB (EN ISO 10140-3)
Castor Chair Suitability:	Yes, Type H (EN ISO 4918)
Dynamic Coefficient of Friction:	>0.60 (EN 13893)
Floor Heating System:	Suitable
VOC Emissions:	Floorscore SC S -FS-03336
Warranty:	10 year commercial
Sustainability:	Floorscore



B.



Scala 090L

Pattern Repeat: 100 x 100cm



Scala 900D

Pattern Repeat: 100 x 100cm



Summer Oak 664D

Pattern Repeat: 200 x 100cm



Willow Oak 602L

Pattern Repeat: 100 x 100cm



Willow Oak 969M

Pattern Repeat: 100 x 100cm



Toledo 6182

Pattern Repeat: 100 x 100cm

Apex



Heavy Commercial



Heavy Residential



Suitable for Staircases



Office Chair Castor Wheels



Underfloor Heating



Natural Look



Anti-Bacterial



Power Bac



Bill of Quantities

- Belgotex's APEX powerbac ± 2.4 mm (total thickness) Heavy Commercial heterogeneous vinyl sheeting.
- 4m width with 0.60mm wear layer.
- 10 year commercial warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.