

B.

Select Plus

Select Plus offers an LVT solution for higher traffic areas. Its 2mm thickness includes a 0.3mm wear layer, and carries a 7-year light commercial & 15-year residential warranty, ideal for creating sophisticated looks in hotel bedrooms and residential spaces.

Extended Specifications

Type of Installation:	Dry Back (Stick Down)
Use Classification:	Medium Commercial
Total Mass:	3550 (g/m²) 114.5 (oz/yd²)
Wear Layer Thickness:	0.3 (mm) 0.0118 (in)
Total Thickness:	2.0 (mm) 0.07 (in)
Tile Size (l x w):	1219.2 × 228.6 (mm) 9 × 48 (in)
Quantity Per Box:	15
Chemical Resistance:	Yes (EN ISO 26987)
Fire Classification:	Bfl-s1 (EN 13501-1)
Slip Resistance:	R10 (DIN 51130)
Residual Indentation:	<0.1mm (EN ISO 24343-1)
Thermal Resistance:	0.027(m²*K)/W



B.

Select Plus

Extended Specifications

Electrostatic Propensity: (Body Voltage Test)	0.1kV (EN 1815 Method A)
Dimensional Stability:	≤0.25% (EN ISO 23999)
Colour Fastness:	>6 Grade (ISO 105-B02)
Sound Absorption:	Approx. 3 dB (EN ISO 10140-3)
Castor Chair Suitability:	Yes, Type W (EN ISO 4918)
Floor Heating System:	Yes, max 27°C
VOC Emissions:	Floorscore SCS-FS-03336
Warranty:	7 year commercial / 15 year residential
Sustainability:	Floorscore



B.



Fab



Chic



Fine



Uber



Rad



Snazzy

Select Plus

Heavy Residential

Medium/General Commercial

COMMERCIAL WARRANTY
7
YEAR

RESIDENTIAL WARRANTY
15
YEAR

Suitable for Staircases

Office Chair Castor Wheels

REUSE
REDUCE
RECYCLE

100% WATER RESISTANT

POLYURETHANE TREATED SURFACE
PU

BN-S1

Natural Look

Anti-Bacterial

Underfloor Heating

E1
MCHO

GREENTAG
CERTIFIED
Level A

bsi
ISO 9001
Quality Management Systems
CERTIFIED

bsi
ISO 14001
Environmental Management
CERTIFIED

bsi
ISO 45001
Occupational Health and Safety Management
CERTIFIED

floor score
CERTIFIED BY SCS Global Services

CE

Bill of Quantities

- Belgotex’s SELECT PLUS is available as ±2.0mm (total thickness) Medium Commercial Use Dry back-stick down LVT vinyl.
- 1219.2 × 228.6mm with 0.3mm wear layer.
- 7 year commercial warranty and 15 year residential warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- GreenTag Level A Gold Rated Certification.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.