## B

## Strut

Strut is a heterogeneous vinyl made for heavy residential applications and boasting realistic designs. This uncompromising product speaks to confidence in materials and in how it deals with traffic, wear and scuffing. Part of a new generation of ready-to-install flooring, Strut is the perfect choice for the modern home as well as retail and hospitality spaces. Offering realistic reproductions of wood and tile designs available in a sheet, this durable, water-resistant and convenient floor is easy to maintain, comfortable underfoot and soundproof. The heterogeneous vinyl is scratch-resistant and slip proof – perfect for families with young children or grandparents – while the hardy and hygienic PU layer is anti-allergenic, which makes it suitable for people living with allergies or pets.

### **Extended Specifications**

Type of Installation:

Use Classification: (EN 1307)

Total Weight: (ISO 23997)

Wear Layer Thickness: (ISO 24340)

Total Thickness: (ISO 24346)

**Product Width:** 

Pattern repeat:

Heterogeneous Vinyl Sheeting

Medium Commerical

1950 (g/m²) | 57.51 (oz/yd²)

0.40 (mm) | 0.015 (in)


2.80 (mm) | 0.110 (in)

2 (m) | 78.74 (in)

(Refer to swatch photography for individual

pattern repeat information)





### **Extended Specifications**

Roll Size:( $l \times w$ ) 30 × 2 (m) | 1181.10 × 78.74 (in)

Backing Type: Black Tex Bac

Chemical Resistance: (EN ISO 26987)

Resistant

Fire Classification: (EN 13501-1)

Bfl-s1

Slip Resistance: (DIN 51130)

Residual Indentation: (EN ISO 24343-1) <0.2mm

Thermal Resistance: (ISO 8302) 0.018m² K/w
Thermal Conductivity: (EN 12524) 0.16 W/m.K

Electrostatic Behaviour: (Body Voltage Test) ≤ 2kV

(EN 1815 Method A)

Dimensional Stability: (EN ISO 23999) ≤0.4%

Colour Fastness: (ISO 105-B02) >6

Sound Absorption: (EN ISO 717/2)  $$\Delta$$  Lw 15 dB Yes, Type W

Dynamic Coefficient of Friction: (EN13893) > 6

Under Floor Heating: (EN 12667) Suitable

Castor Chair Note: Carpet protector mats are necessary where

caster wheels are used.

Warranty: 5 year commercial | 10 year residential



# B



Columbian Oak 636L Pattern repeat: 100cm x 150cm



Columbian Oak 692M Pattern repeat: 100cm x 150cm



Gamble Oak 226M
Pattern repeat:
100cm x 120cm



Gamble Oak 363M Pattern repeat: 100cm x 120cm



Gamble Oak 666D Pattern repeat: 100cm x 120cm



Laurel Oak 663L Pattern repeat: 200cm x 100cm



Oakland 336M Pattern repeat: 100cm x 120cm




Oakland 636D Pattern repeat: 100cm x 120cm



Tasmanian Oak 336M
Pattern repeat:
200cm x 150cm



Verenna 166L Pattern repeat: 200cm x 100cm



Verenna 996E Pattern repeat: 200cm x 100cm


### Strut








Medium/General Commercial



Anti-Bacterial



Suitable for Staircases







**Comfort Bac** 





Heating






















#### **Bill of Quantities**

- · Belgotex STRUT 2.8mm Medium Commercial Use Heterogeneous Vinyl Sheeting.
- $\cdot$  30 × 2m with 0.40mm wear layer.
- 5-year commercial warranty / 10 year residential warranty
- · This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- · Green tag level A Gold rated certification

Note: Belgotex offers customization of this product in colour. Please contact a Belgotex representative for more information.

Product characteristics may vary due to the nature of manufacturing. To combat colour variance do not install more than one dye lot in a single installation. Sample swatches have been cut from an overall design; therefore, the decoration and shades may vary. A difference in appearance from the pattern is likely, as the product is not intended to have a uniform appearance.

\*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.