



Issued on June 2, 2025

PRODUCTION CODE: TBD
Premium Vapour Barrier Film SUPER TEN®

GENERAL DESCRIPTION:

Feature Polyethylene Film for Construction Applications

Coextruded **Feature** construction-grade polyethylene film, engineered with a proprietary blend of extra-strong polyolefins for superior physical properties. This high-performance film complies with **ASTM E1745** Class A, B, and C standards and is certified by an accredited third-party laboratory.

PRODUCT DESCRIPTION:

10 Mil, Premium Vapour Barrier Film SUPER TEN®

Storage Conditions	25°C, 80% RH maximum		
	ASTM	Units	Typical Values
Tensile Strength in MD	E154 Section 9	lbf/in.	>45
Tensile Strength in TD	E154 Section 9	lbf/in.	>45
Puncture resistance	D1709 Method B	grams	>2200
Water Vapor Permeance	E154 Section 7	perms	<0.1
Thickness – Average	D6988 Method A	Mil	10

Disclaimer:

This information represents our best judgment based on work done in our lab, but the company assumes no liability whatsoever in connection with the use of information or findings contained herein. Customers need to confirm the performance in their own specific application environment to validate fit for use”.

**QUALITY MANAGEMENT SYSTEM
ISO 9001
REGISTERED**

**GLOBAL FOOD SAFETY INITIATIVE (GFSI)
FOOD SAFETY SYSTEM FSSC 22000
REGISTERED**