



Soften Acoustic tour

Rima



Sound absorption

Class B

Fire classification

B-s1, d0

Material classification

M1

Raw materials:

Natural / approved

Mitat ja materiaali

Measures and Material

Maksimi korkeus

2950 mm.

Maksimi leveys

1290 mm.

Materiaali

Materiaalina kotimainen 100% polyesterihuopa, jonka valmistuksessa hyödynnetään kierrätettyjä Pet-pulloja. Valmistus ilman kemikaaleja ja liuottimia.

Asennus

Yksinkertaisimmillaan asennus toteutetaan kiilalistakiinnityksellä, jolloin koko elementti nostetaan seinään kiinnitetyn kiilalistan päälle. Muita kiinnitystapoja ovat esimerkiksi tarranauhakiinnitys, liimaus, naulaus ja ruuvaus.

Max height

2950 mm.

Max width

1290 mm.

Material

The material is domestic 100% polyester felt, made using recycled PET bottles. Manufactured without chemicals and solvents.

Installation

At its simplest, installation is done using a wedge strip mount, where the entire element is lifted onto a wedge strip attached to the wall. Other mounting options include velcro fastening, gluing, nailing and screwing.

Vakiovärit

Valkoinen

Greige

Vaaleanharmaa

Tummanharmaa

Musta

Tilausvärit

Saatavana myös kangasverhoiltuna. Verhoilukankaaksi on valittavissa useita vaihtoehtoja esimerkiksi Gabrielin, Camiran ja Nevotexin mallistoista.

Standard colors

White

Greige

Light grey

Dark grey

Black

Special colors

Also available with fabric upholstery. A wide range of fabric options can be selected from collections such as Gabriel, Camira and Nevotex.

soften® ACOUSTIC SOLUTIONS



02-534 4440
myynti@soften.fi

Soften Oy • Kärämäentie 35 • 20360 Turku • Finland