



BOA



- Submersible to 22.5 m above deck
- Heavy cargo up to 57.500 t
- Voluminous cargo up to 11.750 m³
- Extreme deck strength of 35 t/m²
- ICE-C class
- Hybrid power system

BOA BARGE 39/40

Semi Submersible Heavy Lift and
Launching Cargo Barge



BOA BARGE 39/40

General Information

Vessel's Name	BOA BARGE 39
Flag	Norwegian, NOR
Class Society	DnV
Class Notations	+1A, Barge for deck cargo DAT (-10°C) ICE C
Year built	2026
Builder	PRC
Place built	PRC
Owner	Boa Barges AS
Manager	Boa Management AS

Dimensions

Length, Overall	166 m
Breadth, Moulded	73.38 m
Depth, Moulded	9.15 m
Draught load line (transit) approx.	6.53 m
Design draught (submerged)	31.65 m for, 31.65 m aft
Air Draught (from keel to top of mast)	39 m
Web Frame Spacing	2 m
Long. Stiffener Spacing	0.61 m
Gross Tonnage	111.784 t
Net Tonnage	33.643 t

Cargo Capacities

Deadweight (T = 6.53 m)	57.500 t
Deck space	11.750 m ²
Deck strength	35 t/m ²
Launching Capacity	up to 10.000 t jacket

Submerging Depth

Submerging	22.5 m above deck
Floating towers (4 off) for free floating submerging operations (Removable)	LxBxH: 10 m x 5.49 m x 25 m

Tank Capacities

Ballast tanks	99.274 m ³
Bilge tanks	33 m ³
Sewage	2 x 21 m ³
Fresh water	2 x 22 m ³
Fuel (MDO)	46 m ³
Lub. Oil Store	0.6 m ³
Hydr. Oil Store	1.2 m ³
Misc. Oil Store	0.6 m ³

Ballast System

Main Ballast Pumps (Electric Driven)	4 x 5250 m ³ /hr
Aft Ballast Pumps (Electric Driven)	2 x 750 m ³ /hr
Service Pump (Electric Driven)	1 x 400 m ³ /hr
Ballast Tanks	28 in pontoon, 2 in deck-house
Remote operated pumps, valves and sounding system from control -and engine room.	
Ejector stripping system for all ballast tanks	

Power Supply

Main Generators	3 x 590 kVA, 440 V, 60 Hz 1 x 129 KvA, 440 V, 60 Hz
Work Generator	1 x 60 kVA, 440 V, 60 Hz
Shore Power Connections	230 V and 400-440 V
Deck Distribution for clients equipment	230 V and 440 V, 60Hz
Ligths powered by solar panels	

Anchor & Mooring Equipment


Anchor Winches	2 x hydraulic winches
Anchors	2 x SPEK 8300 kg, 2 x 330 m x 70 mm K3
Capstans	4 x 15 t pull
Work Winches	2 x single drum +2 x double drum on winch deck
Rope Capacities	220 m x 40 mm 150 m x 60 mm
Electrical winches on top of floating towers Rope capacities of 220 m x 40mm/150 m x 60 mm	
Bollards	Capacity SWL 150-200 t

Towing Equipment


Towing Bridle	Each legs 27.5 m, tow plate and 12 m long fore runner
Bridle Chain	K3, MBL 5780 KN, Max. Bollard Pull 275 t
Recovery System	Recovery winch and A-frame with chain on forecastle deck
Towing Brackets	2 forward 750 t MBL
Towing Connections	2 aft 750 t MBL

Accommodation


Accommodations	32 beds
Cabins	16
Day Room	1
Meeting Room	1 for 12 persons




DECK PLAN VIEW




SIDE VIEW



BOW VIEW



STERN VIEW



A DECK


B DECK

C DECK

D DECK

E DECK


01 DECK



02 DECK

WINCH DECK

OBSERVATION DECK





CORPORATE HEADQUARTERS

BOA Management AS
Strandveien 43
7067 Trondheim
Norway
+47 73 99 11 99
chartering@boa.no

www.boa.no

Every effort has been made to ensure that all information contained in this brochure is accurate and up-to-date, however all specifications are subject to change without notice and should be verified. Boa accepts no liability or responsibility for any action taken based on the information presented in this brochure. Boa encourages interested parties to verify the contents of this brochure when in doubt.