



DATA SHEET

Modèle : JUPITER DC 40KW

Item Combo CCS2

Input

Power Supply 3P+N+PE
Rated Voltage AC260 ~ 475V
Rated Current 3x64A
Frequency 50/60 Hz

Output

Output Voltage DC200 ~ 1000V
Maximum Current 133A
Rated Power 40KW (Adjustable up to 40 KW MAX)
Efficiency 95%

User Interface

Gun cable length 5 meters
Material Galvanized sheet powder-coated metal housing
Colour White
5-inch LCD screen ✓
Power Meter MID ✓
ISO 15118 ✓
4G ✓
Ethernet ✓
RFID ✓
OCPP 1.6 ✓

Safety

Ingress Protection IP54
Over Current Protection ✓
Residual Current Protection (AC30mA) ✓
Over / Under Voltage Protection ✓
Over Temperature ✓
Certification CE / UKCA / RoHS
Certification Standard EN IEC 61851, SI 2016

Environment

Installation Wall Mounted
Mounting Options Mounting post
Work temperature -25 C ~ 50 C
Work Humidity 3% ~ 95%
Work Altitude <2000m

Colisage

Production Dims (H*W*D)mm 760*560*280
Package Dims (L*W*H)mm 940*640*570
Net weight (kg) 70
Gross weight (kg) 89