


AHD-DPS02 B28 / B35 / B42 Control Unit

Position and Signal Lights Control and Monitoring



- **Compact control unit for position and signal lantern control**
AHD-DPS02 G14 / AHD-DPS02 A07
- **Standard panel with 28, 35, or 42 switching channels and free labeling fields**
- **Additional LED indicators for supply and system errors as well as for lamp life warning message**
- **Automatic dimming of LED indicators, adjustable**
- **Integrated alarm buzzer and acknowledgment button**
- **Optional release switch for activating operating authorization**
- **Direct connection to basic module AHD-DPS02 G14 and expansion modules AHD-DPS02 A07 via pre-assembled ribbon cable**
- **Module housing for installation in desks, consoles, or switchboards, Front dimensions 294 mm x 150 mm, protection class IP20**
- **Approvals: ABS, BV, CRS, DNV, LR, PRS, RINA**



Description

The AHD-DPS02 system is used to control and monitor position and signal lights on ships.


AHD-DPS02 B14 and AHD-DPS02 B21 are control panels for controlling up to 28, 35 or 42 lamp channels with free labeling fields in a standardized design.

The control unit has front buttons for direct lamp control and optical feedback to signal a lamp failure. The device is connected directly to the AHD-DPS02 G14 base module and the AHD-DPS02 A07 expansion modules via ribbon cable.


AHD-DPS02 B28 / B35 / B42 - Dimensions and view



AHD-DPS 02 B35 Front View (Frontansicht)



AHD-DPS 02 B28 Front View (Frontansicht)



AHD-DPS 02 B42 Front View (Frontansicht)



Technical data

AHD-DPS02 B28 / B35 / B42

Power supply 24 V DC (+30% / -25%)
(via AHD-DPS02 G14)

Current consumption

AHD-DPS02 B28 50..200 mA (typ.)

AHD-DPS02 B35 50..250 mA (typ.)

AHD-DPS02 B42 100..300 mA (typ.)

Operating temperature -25 °C...70 °C

Storage temperature -30 °C...85 °C

Weight

AHD-DPS02 B28 Approx. 0.75 kg

AHD-DPS02 B35 Approx. 0.8 kg

AHD-DPS02 B42 approx. 0.85 kg

Protection class IP 20

External dimensions 294 x 150 x 98 mm

Cutout 283 x 138.5 mm

Input/Output

AHD-DPS02 B28 3x serial (1x base module,
2x expansion modules)

AHD-DPS02 B35 4x serial (1x base module,
3x expansion module)

AHD-DPS02 B42 5x serial (1x base module,
4x expansion module)

Installation Desk or wall mounting

Approvals ABS, BV, CRS, DNV, LR, PRS, RINA

Item no.:

AHD-DPS02 B28 12521V3 (28 switches)

AHD-DPS02 B35 12522V3 (35 switches)

AHD-DPS02 B42 12382V3 (42 switches)