



BLACK LOCUST LUMBER

Deck Tiles — Spec Sheet

FOR ARCHITECTS, LANDSCAPE DESIGNERS & HOMEOWNERS

SECTION 01


Deck tile sizes

2 × 2

2 ft × 2 ft modular tile

FINISHED DIMENSIONS

23-7/8" × 23-7/8" · 1-11/16" tall



2 × 4

2 ft × 4 ft modular tile

NOMINAL DIMENSIONS

24" × 48" · 1-11/16" tall




Available in 2×2 and 2×4 formats. All material is air dried, preserving Black Locust's natural stability and minimizing checking, warping, and honeycombing while keeping the wood's strength and appearance.

SECTION 02

Tile anatomy

Solid Black Locust, built to a system.



8 TOP SLATS · 3 BOTTOM SUPPORTS
PRE-DRILLED CORNERS



EDGE
1-11/16" tall
3 support slats

SLAT COUNT

8 top · 3 bottom support

WOOD THICKNESS

13/16"

SLAT PROFILE

S4S, trimmed & end-sealed

SLAT WIDTH · SPACING

2-7/8" · 3/16" gap

TILE HEIGHT

1-11/16"

FASTENERS

305-grade stainless screws

CORNERS

Pre-drilled, compatible with DeckWise® connectors & pedestals

Pre-drilled corner holes accept DeckWise® Deck Tile Connectors and Altitudes Pedestal® pine-tree fasteners. ≈ 21 lbs per 2×2 tile · Class A fire rated (ASTM E84-16) · 1,700 Janka.

SECTION 03

Installation accessories

AUTHORIZED DECKWISE® DEALER



DeckWise® Deck Tile Connector System

Snap-in polyethylene connectors that lock tiles together, set a precise 3/8" gap, and elevate tiles for airflow and drainage on flat solid surfaces. ≈ 1.25 connectors per tile.

Best for: low-profile installs on concrete, balconies, rooftops, and existing decks.



DeckWise® Altitudes Pedestal® System

Adjustable screw-jack pedestals that build perfectly level decking over sloped or uneven rooftops and plazas, with no sub-framing required. Heights 1-1/2" to 24", compensates 0–5% slope, rated to 1,200 lbs per pedestal. Integrated 3/16" spacer tabs set tile gaps automatically.

Best for: elevated, sloped, or rooftop applications over uneven substrates.

Choose connectors for low-profile installs on solid surfaces; choose Altitudes pedestals for elevated, sloped, or rooftop applications. Both fasten directly into the tiles' pre-drilled corners.



BLACK LOCUST LUMBER

Honest, durable, useful hardwood, milled and graded by hand.

888 · 501 · 0678

SALES@BLLPRO.COM · BLACKLOCUSTLUMBER.COM