



SECTION 01

Decking sizes

 $5/4 \times 4$

5/4" thick 4" wide

FINISHED DIMENSIONS 1" X 3.5"

 $5/4 \times 6$

5/4" thick 6" wide

FINISHED DIMENSIONS 1" X 5.5"

RL

3 – 8 FT

6 ft

SET

8 ft

SET

10 ft

SET

12 ft

SET

RL = mixed 3–8 ft bundle. Set lengths at 6, 8, 10, 12 ft.

All material is air dried. Air drying preserves Black Locust's natural stability and durability by reducing internal stresses that can develop during aggressive kiln drying. Because Black Locust is a dense, tension-prone species, air drying helps minimize checking, honeycombing, and warping while maintaining the wood's natural strength and appearance.


SECTION 02

Choose your profile

Eased radius edge



Boards face-screwed with stainless steel; holes left exposed or filled with matching black locust plugs.




- Face-screw installation
- Plug or expose screw heads
- Available in all sizes & lengths

Hidden fastener groove



DeckWise® Extreme S® clip seats into grooves on both edges, hides every fastener, and self-spaces boards at 5/32" (4 mm).



- No visible fasteners
- DeckWise® Extreme S® clip system
- 5/32" auto-spaced board gap

Both profiles available in $5/4 \times 4$ and $5/4 \times 6$ · all lengths.

SECTION 03

Decking accessories

AUTHORIZED DECKWISE® DEALER

01

**DeckWise® Extreme S® clip**

Stainless hidden-fastener clip. Seats in the groove, auto-spaces at 5/32", single screw.

100 ct · 175 ct

02

**Stainless deck screws**

For face installs. Trim-head or bugle-head, stainless. Pre-drill required; holes may be plugged.

Multiple lengths

03

**WiseWrap® JoistTape™**

Self-adhesive butyl barrier applied to joist tops. Blocks moisture from reaching the framing.

3" × 75 ft roll

04

**Drill & Drive™ kit**

DeckWise three-in-one bit set: pre-drill, countersink, and drive. Flip the bit, no tool swap.

10-piece bit set

05

**Hardwood plug cutters**

Cuts matching black locust plugs on-site to fill countersunk holes. Self-centering geometry.

3/8" & 1/2" sizes

06

**Anchorseal® 2**

Hybrid wax emulsion brushed onto fresh end grain. Prevents up to 90% of end checking.

1 qt · 1 gal · 5 gal