



Polymeric cut vinyls with a high tack permanent adhesive and air-egress liner. Thanks to the unique combination of the high tack adhesive with air-egress liner, CV300 Series™ ensures **easy, dry application on a wide variety of substrates.**

CV300 Series™

Soft in nature, CV300 Series™ calendared opaque vinyls are films with excellent dimensional stability, suitable for flat, slightly curved and mildly textured surfaces

Effortless cutting and weeding

Easy to dry-apply

Adheres to difficult surfaces*

High opacity

Rolls of 1220mm x 45,7m

For ease of installation, apply CV300 Series™ cut vinyl with RTape Conform® 4761RLA application tape for air-egress liners

* On hard-to-adhere surfaces, we recommend a test to confirm that the vinyl will bond before full application.

** Vertical exposure, Mid-EU climate

Applications

- Indoor lettering
- Wall decorations & decals
- Window signage
- Event signage
- P.O.P. signage
- In-Store promotions

PRODUCT OVERVIEW ►

GLOSS



BLACK



WHITE



BLUE



HUNTER GREEN



CARDINAL RED



ORANGE



DARK GREY



SUNFLOWER YELLOW



BRIGHT YELLOW

MATT



BLACK



WHITE



MEDIUM BLUE



HUNTER GREEN



CARDINAL RED



ORANGE




DARK GREY



SUNFLOWER YELLOW



SILVER



GOLD

Colour	SKU #	Size
Gloss		
Black	EC3745-48150	1220mm x 45,7m
White	EC3281-48150	1220mm x 45,7m
Blue	EC7112-48150	1220mm x 45,7m
Hunter Green	EC8778-48150	1220mm x 45,7m
Cardinal Red	EC2472-48150	1220mm x 45,7m
Orange	EC5555-48150	1220mm x 45,7m
Dark Grey	EC1270-48150	1220mm x 45,7m
Sunflower Yellow	EC4267-48150	1220mm x 45,7m
Bright Yellow	EC3048-48150	1220mm x 45,7m

Colour	SKU #	Size
Matt		
Black	EC9284-48150	1220mm x 45,7m
White	EC1955-48150	1220mm x 45,7m
Medium Blue	EC7288-48150	1220mm x 45,7m
Hunter Green	EC4325-48150	1220mm x 45,7m
Cardinal Red	EC9882-48150	1220mm x 45,7m
Orange	EC7422-48150	1220mm x 45,7m
Dark Grey	EC9012-48150	1220mm x 45,7m
Sunflower Yellow	EC1986-48150	1220mm x 45,7m
Silver	EC1982-48150	1220mm x 45,7m
Gold	EC3477-48150	1220mm x 45,7m



CV300 Series™ is a high-end multipurpose cut vinyl suitable for letterings and decals on walls, windows and other storefronts.

TECHNICAL DATA ►

Physical Properties		
Film		Polymeric calendared vinyl
Adhesive		High tack permanent acrylic
Liner		165gsm kraft air Egress
Opacity		92% min
Thickness	Film	75 micron
	Film + adhesive	100 micron
Adhesion	Stainless steel - 20min	20 N/25mm
	Stainless steel - 24hrs	24 N/25mm
Weight	Film + Adhesive	125-130 gsm
	Total w/Liner	280-290 gsm

Conditions for use	
Shelf Life*	2 year
Outdoor Durability**	Up to 5 years for Black/White Up to 4 years for other colours
Min Application Temp	+2°C
Service Temp	-24°C to +60°C
Solvent Resistance***	Good for most petroleum-based solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended.
Water Resistance	Excellent

* Stored at 22°C /50-55%RH

**Vertical exposure, Mid-EU climate

*** For ultimate solvent resistance, edge sealing is recommended.