

Glass Finishes® Horizontal Lines Gradient

A durable polyester film featuring a white striped gradient effect, starting at the bottom with thicker white lines that gradually become thinner and fade to clear toward the top. Ideal for glass partitions or windows that provide privacy at a lower level while maintaining light and openness above.

FACE FILM

Polyester

| | |
|----------------|-----------------------------|
| Thickness (µm) | 50 |
| Finish | Matt white stripes gradient |

ADHESIVE

Clear acrylic, removable

| | |
|----------------|----|
| Thickness (µm) | 50 |
|----------------|----|

RELEASE LINER

Clear siliconized synthetic liner

| | |
|----------------|----|
| Thickness (µm) | 50 |
|----------------|----|

PRODUCT APPLICATION

| | |
|------------------------------|----------|
| Application method | Wet |
| Application temperature (°C) | 10 to 30 |
| Indoor/outdoor windows | Indoor |

DURABILITY

| | |
|---------------------------|----|
| Shelf life (months) | 24 |
| Indoor durability (years) | 8 |

CERTIFICATES

| | |
|-------------|----------------------|
| Fire rating | EN 13501-1 (Class B) |
|-------------|----------------------|

ROLL SIZES

1520mm x 30m

Nekoosa Coated Products, LLC guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Nekoosa Coated Products, LLC guarantees that the products are free from defects in workmanship or defects in Nekoosa material, provided they are stored properly. At its sole discretion, Nekoosa Coated Products, LLC may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.