

Glass Finishes® Reeded Glass Film (12,7mm)

A durable polyester film that simulates the look of real reeded glass, providing privacy and a sleek decorative effect for glass partitions or windows.

FACE FILM

Polyester

Thickness (µm)	50
Finish	Clear reeded (12,7mm)

ADHESIVE

Clear UV-cured acrylic, removable

Thickness (µm)	50
----------------	----

RELEASE LINER

Clear siliconized synthetic liner

Thickness (µm)	50
----------------	----

PRODUCT APPLICATION

Application method	Wet
Application temperature (°C)	10 to 30
Indoor/ outdoor windows	Indoor

DURABILITY

Shelf life (months)	24
Indoor durability (years)	8

CERTIFICATES

Fire rating	EN 13501-1 (Class B)
-------------	----------------------

ROLL SIZES

1520mm x 30m

Nekoosa Coated Products, LLC guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Nekoosa Coated Products, LLC guarantees that the products are free from defects in workmanship or defects in Nekoosa material, provided they are stored properly. At its sole discretion, Nekoosa Coated Products, LLC may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.