

Wall Graphics® White

Wall Graphics® is a white calendared vinyl for short-term indoor and outdoor wall graphic applications. The repositionable adhesive allows easy positioning during installation and clean removability (up to 1 year).

FACE FILM

Calendred vinyl

Thickness (µm)	140
Finish	Matt white

ADHESIVE

Microsphere adhesive, removable

Thickness (µm)	20
Adhesion to steel	FINAT FTM 1
20 minutes (180°) N/25mm	5
24 hours (180°) N/25mm	7

RELEASE LINER

Kraft paper liner, lay-flat

Weight (gsm)	145
--------------	-----

PRODUCT APPLICATION

Application method	Dry
Application temperature (°C)	-30 to 65

DURABILITY

Shelf life (months)	12
Outdoor durability (years)	3
Solvent resistance	Good
Water resistance	Excellent

ROLL SIZES

1370mm x 45,7m

ROLL PRINTING METHOD

(Eco-)solvent, UV & latex

Nekoosa Coated Products, LLC guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Nekoosa Coated Products, LLC guarantees that the products are free from defects in workmanship or defects in Nekoosa material, provided they are stored properly. At its sole discretion, Nekoosa Coated Products, LLC may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.