

Technical Data Sheet

Pyrotape®

Product Name: Pyrotape®

Technical Description: White knitted fiberglass yarn woven to produce a flat strip that is coated on one side with thick covering of iron oxide red silicone rubber.

Temperature Capabilities: Rated for 500°F (260°C) continuous exposure, up to 2000°F (1093°C) for 15 to 20 minutes and up to 3000°F (1650°C) for 15 to 30 seconds.



Product Overview: Pyrotape® is designed to provide a non-adhesive insulating wrap that can be used as a substitute for Pyrojacket® protecting assemblies without disconnection of the hose or cable assembly. Pyrotape® offers excellent resistance to molten metal splash, radiant heat, abrasion, corrosive atmosphere, moisture, chemicals, vibration, and electricity.

Dimensional Data: Available in 1", 2", 3", 4", and 5" (25mm, 50mm, 76mm, 102mm, and 127mm) widths. Standard lengths are 50ft (15m) and 100ft (30 m).

Nominal Thickness: 0.147" (3.73mm)

Installation: A 30 to 50% overlap is recommended, using Pyrosil™ Tape or stainless steel ties to hold tape in place.

Cautionary Notes: Not recommended for severe dynamic flexing applications unless firmly clamped in place.

Disclaimer: Due to the range of possible applications, no warranty is expressed or implied. ADL Insulflex, Inc.'s liability is limited solely to the replacement of defective material. ADL Insulflex, Inc. will not be held liable for any consequential damages arising from the use or misuse of the material. While the information given herein is believed to be reliable, ADL Insulflex, Inc. makes no warranties as to the accuracy or completeness. Samples of all Insulflex® products are available at no cost or obligation, and suitable trials should be made prior to installation.

Telephone

North America: (800) 461-9323
International: (905) 377-1488

ADL Insulflex, Inc.

94 Wilmott Street
Cobourg, ON
K9A 0E9

Fax

North America: (800) 461-9328
International: (905) 377-1484