

Technical Data Sheet

Silicaflex™ Tape AB

Product Name: Silicaflex™ Tape AB

Technical Description: A slit Silica tape, designed to protect hoses, cables, and tubing from intense radiant heat and flame. Coated with a pressure-sensitive adhesive on one side to facilitate wrapping.

Temperature Capabilities: Rated for 1800°F (982°C) continuous. 2300°F (1260°C) intermittent exposure.



Product Overview: Silicaflex™ Tape AB is constructed by slitting full rolls of Silica cloth that have been coated with a pressure sensitive adhesive.

Silicaflex™ textiles are an excellent alternative to asbestos for protecting hoses, cables, and other equipment from extreme heat, molten metals, sparks and flame in a wide range of iron and steelmaking, welding, burning, cutting, and heat treating operations. Silicaflex™ textiles resist most corrosive fluids and generate virtually no smoke or fumes even under the most severe heat conditions. Slit tapes such as Silicaflex™ Tape AB are coated to improve low-temperature handling properties and minimize raveling. Both the coating and the pressure-sensitive adhesive will decompose at high temperatures.

Dimensional Data:

Available in 2" (51mm), 3" (76mm), and 4" (102mm) wide tapes, .030" (.76mm) thickness.
Also Available in .060" (1.52mm) thickness.

Installation: May be installed only on clean surfaces. Depending on the desired wall thickness, a spiral overlap may be used to increased thickness and aid integrity of the installation. In most cases a 50% overlap is recommended.

Cautionary Notes: All silica textiles exhibit poor resistance to molten alkalis, and have fair to moderate abrasion resistance. In applications where severe abrasion is a factor, a secondary covering is recommended.

Disclaimer: Due to the range of possible applications, no warranty is expressed or implied. ADL Insulflex, Inc.'s liability is limited solely to the replacement of defective material. ADL Insulflex, Inc. will not be held liable for any consequential damages arising from the use or misuse of the material. While the information given herein is believed to be reliable, ADL Insulflex, Inc. makes no warranties as to the accuracy or completeness. Samples of all Insulflex® products are available at no cost or obligation, and suitable trials should be made prior to installation.

Telephone

North America: (800) 461-9323
International: (905) 377-1488

ADL Insulflex, Inc.

94 Wilmott Street
Cobourg, ON
K9A 0E9

Fax

North America: (800) 461-9328
International: (905) 377-1484