

## Technical Data Sheet

### Flexgard™ VCO

**Product Name:** Flexgard™ VCO

**Technical Description:** Flexgard™ VCO is a woven nylon sleeve with a hook-and-loop closure.

**Temperature Capabilities:** Flexgard™ VCO is rated for 250°F (121°C) continuous exposure with excellent U.V. protection. It has excellent moisture resistance which makes it ideal for use outdoors. Low temperature rating is -20°F (29°C).



**Product Overview:** Flexgard™ VCO sleeve can be easily installed over hoses, cables, tubing or pipes. The urethane coating over nylon offers excellent resistance to abrasion, UV, moisture, chemicals, and vibration. Flexgard™ VCO hook-and-loop closure system is ideal for retro fits, reducing installation labour time by up to 70%.

**Dimensional Data:** Sizes range from 1" (25mm) ID up to 8" (200mm) ID. Standard roll lengths available in 75ft (22.5m) and 150ft (45m). Custom diameters and lengths also available.

#### Property Data:

Weight: 14.5oz /sq yd

Coating: 80g PU

Tensile Strength (Warp/Fill): 987lb x 758lb ASTM D5034

Tear Strength (Warp/Fill): 236lb x 200lb ASTM D2261

**Installation:** Allow tolerance to install over hoses or cables.

#### Cautionary Notes: N/A

**Disclaimer:** Due to the range of possible applications, no warranty is expressed or implied. ADL Insulflex, Inc.'s liability is limited solely to the replacement of defective material. ADL Insulflex, Inc. will not be held liable for any consequential damages arising from the use or misuse of the material. While the information given herein is believed to be reliable, ADL Insulflex, Inc. makes no warranties as to the accuracy or completeness. Samples of all Insulflex® products are available at no cost or obligation, and suitable trials should be made prior to installation.

#### Telephone

**North America:** (800) 461-9323

**International:** (905) 377-1488

#### ADL Insulflex, Inc.

94 Wilmott Street

Cobourg, ON

K9A 0E9

#### Fax

**North America:** (800) 461-9328

**International:** (905) 377-1484