

INSULFLEX[®]

Solving High-Temperature Problems Worldwide


Technical Data Sheet

Pyreflect[™] Blanket

Product Name: Pyreflect[™] Blanket

Technical Description: A highly reflective engineered blanket. This blanket has a mylar surface applied onto one side of an aramid substrate. The aramid substrate is a blend of both Kevlar[®] and Nomex[®].

Temperature Capabilities: Rated for 650°F (343°C) continuous, 1000°F (537°C) intermittent radiant heat.



Product Overview: Pyreflect[™] is designed to reflect radiant heat and exhibit the properties of flexibility, abrasion resistance, toughness, and tensile strength, and is impervious to most liquids, including those with a hydrocarbon base. The Kevlar[®]/Nomex[®] inner core offers excellent long-term heat resistance. The mylar aluminization on the outer surface reflects the majority of the radiant heat, minimizing the heat energy transfer through the blanket.

Dimensional Data: Available in 20oz/y² (678grams/mtr²) weight – coated 1 side only
Roll Width Available : 40" (1016 mm)/ 58" (1473mm)
Nominal Thickness: 0.050" (1.27mm)
Breaking Strength – Warp: 250lbs/inch
Supplied in custom lengths to meet application requirements up to 150ft (45m)

Low Temp. Resistance: No breaking, shattering, or cracking of the coating after conditioning for 4 hours at -20°F (-29°C).

Installation: Depends on a wide variety of application parameters.

Cautionary Notes: Not recommended for extreme molten splash applications.

Disclaimer: Due to the range of possible applications, no warranty is expressed or implied. ADL Insulflex, Inc.'s liability is limited solely to the replacement of defective material. ADL Insulflex, Inc. will not be held liable for any consequential damages arising from the use or misuse of the material. While the information given herein is believed to be reliable, ADL Insulflex, Inc. makes no warranties as to the accuracy or completeness. Samples of all Insulflex[®] products are available at no cost or obligation, and suitable trials should be made prior to installation.

Telephone
North America: (800) 461-9323
International: (905) 377-1488

ADL Insulflex, Inc.
94 Wilmott Street
Cobourg, ON
K9A 0E9

Fax
North America: (800) 461-9328
International: (905) 377-1484

www.adlinsulflex.com