

GRID-TIED INVERTER

THREE-PHASE: GT3-36/40/50/60/75KL1
GT3-36/40/50/60/75KL11, GT3-60KL12

INVERTER

Model	GT3-36KL1	GT3-40KL1	GT3-50KL11	GT3-60KL12	GT3-36KL11	GT3-40KL11	GT3-50KL1	GT3-60KL11	GT3-75KL11	GT3-60KL1	GT3-75KL1
PV Input											
Max. DC Input Power [Wp]	54000	60000	75000	90000	54000	60000	75000	90000	112500	90000	112500
Max. DC Input Voltage[V]	800										
Min. PV Input Voltage[V]	180										
Start-up DC Input Voltage[V]	200										
Nominal DC Input Voltage[V]	370										
MPPT Operating Range[V]	180 ~ 700V										
Max. DC Input Current[A]	4*40				6*40				8*40		
Max. Short Circuit Current[A]	4*52				6*52				8*52		
No. of MPPTs	4				6				8		
No. of Strings per MPP Tackers	4*2				6*2				8*2		
AC Output											
Nominal Output Power [W]	36000	40000	50000	60000	36000	40000	50000	60000	75000	60000	75000
Max. Apparent Power [VA]	39600	44000	55000	66000	39600	44000	55000	66000	75000	66000	75000
Rated AC Grid Output Current[A]	94.5	105	131.2	157.5	94.5	105	131.2	157.5	196.8	157.5	196.8
Max. AC Output Current[A]	103.9	115.5	144.3	173.2	103.9	115.5	144.3	173.2	196.8	173.2	196.8
Rated AC Grid Voltage[V]	3 / (N) / PE, 220										
AC Grid Voltage RangeØ[V]	176 ~ 264										
Rated Grid Frequency [Hz]	50 / 60										
Grid Frequency RangeØ[Hz]	55 ~ 65										
Power Factor	> 0.99 at rated power (Adjustable 0.8 Leading ~ 0.8 Lagging)										
THDi	<3% at rated power										
Efficiency											
Max. Efficiency[%]	98.50%										
Euro Efficiency[%]	98.30%										
MPPT Efficiency[%]	>99%										
Protection											
Integrated DC Switch	Support										
DC Reverse Polarity Protection	Support										
Surge Protection	Type II										
PV Current Detection	Support										
Insulation Resistor Detection	Support										
Output Over Current Protection	Support										
AC Short Circuit Protection	Support										
Output Over Voltage Protection	Support										
Anti-islanding Protection	Support										
Temperature Protection	Support										
Ground Fault Monitoring	Support										
Internal Over Voltage Protection	Support										
Input Over Current Protection	Support										
Grid Monitoring	Support										
Integrated PID Recovery	Support										
Residual Current Monitoring Unit	Support										
AFCI Protection	Optional										
General Data											
Dimensions(W*H*D) [mm]	960*725*369 mm										
Weight [kg]	87 kg										
Mounting Information	Wall Mounting										
Protection Degree	IP66										
Operating Temperature Range [°C]	-30 °C to +60 °C (derating at 45°C)										
Relative Humidity	0 ~ 100%										
Max. Operating Altitude[m]	4000(≥3000) derating										
Night Self Consumption [W]	<5										
Display	LED+APP										
Communication	RS485, Wi-Fi										
Topology	Transformerless										
Certifications and Standards											
Grid Regulation	IEC61727, IEC62116										
Safety	IEC62109-1 / -2										
EMC	EN61000-6-1 / 2 / 3 / 4										

GRID-TIED INVERTER

THREE-PHASE: GT3-100/124/125/150KM1
GT3-100/124/125KM11

INVERTER

Model	GT3-100KM11	GT3-124KM11	GT3-125KM11	GT3-100KM1	GT3-124KM1	GT3-125KM1	GT3-150KM1
PV Input							
Max. DC Input Power [Wp]	150000	186000	187500	150000	186000	187500	225000
Max. DC Input Voltage[V]				1100			
Min. PV Input Voltage[V]				180			
Start-up DC Input Voltage[V]				200			
Nominal DC Input Voltage[V]				720			
MPPT Operating Range[V]				180 - 1000			
Max. DC Input Current[A]	8*40			10*40			
Max. Short Circuit Current[A]	8*52			10*52			
No. of MPPTs	8			10			
No. of Strings per MPP Tackers	8*2			10*2			
AC Output							
Nominal Output Power [W]	100000	124000	125000	100000	124000	125000	150000
Max. Apparent Power [VA]	110000	124000	137500	110000	124000	137500	165000
Rated AC Grid Output Current[A]	120.3	149.2	150.4	120.3	149.2	150.4	180.4
Max. AC Output Current[A]	132.2	149.2	165.4	132.2	149.2	165.4	198.5
Rated AC Grid Voltage[V]	3 / (N) / PE, 277 / 480						
AC Grid Voltage RangeØ[V]	408 - 528						
Rated Grid Frequency [Hz]	50 / 60						
Grid Frequency RangeØ[Hz]	55 - 65						
Power Factor	> 0.99 at rated power (Adjustable 0.8 Leading - 0.8 Lagging)						
THDi	<3% at rated power						
Efficiency							
Max. Efficiency[%]	98.80%						
Euro Efficiency[%]	98.40%						
MPPT Efficiency[%]	>99%						
Protection							
Integrated DC Switch	Support						
DC Reverse Polarity Protection	Support						
Surge Protection	Type II						
PV Current Detection	Support						
Insulation Resistor Detection	Support						
Output Over Current Protection	Support						
AC Short Circuit Protection	Support						
Output Over Voltage Protection	Support						
Anti-islanding Protection	Support						
Temperature Protection	Support						
Ground Fault Monitoring	Support						
Internal Over Voltage Protection	Support						
Input Over Current Protection	Support						
Grid Monitoring	Support						
Integrated PID Recovery	Support						
Residual Current Monitoring Unit	Support						
AFCI Protection	Optional						
General Data							
Dimensions(W*H*D) [mm]	960*725*369						
Weight [kg]	≤ 86						
Mounting Information	Wall Mounting						
Protection Degree	IP66						
Operating Temperature Range [°C]	-30 °C to +60 °C (derating at 45°C)						
Relative Humidity	0 - 100%						
Max. Operating Altitude[m]	4000(±3000) derating						
Night Self Consumption [W]	<5						
Display	LED+APP						
Communication	RS485, Wi-Fi						
Topology	Transformerless						
Certifications and Standards							
Grid Regulation	IEC61727, IEC62116, IEEE1547						
Safety	UL1741, IEC62109-1 / -2						
EMC	EN61000-6-1 / 2 / 3 / 4						