

## ALL-IN-ONE ESS

### HBP1800 Series

1.2~3KW | 12V, 24V | 1280Wh~7168Wh

MUST HBP1800 series all-in-one energy storage solution, support 1.2~3KW output for different load appliances. It's based on the original cabinet design, stacked with solar energy storage lithium battery 1280wh~7168wh, and built in battery protection system, fully retain the use of load power in applications of residential, school, commercial and public utility area.



- 1.2~3KW Pure sine wave inverter
- Energy storage 1280wh~7168wh Optional
- 4000+ Charge cycle @ 80% DOD,25°C
- 24/7 Plug & play
- 11 Output ports for DC load
- Built in Multi safety protection



Features higher capacities for greater compatibility with more power-hungry devices, and the latest in USB-C Power Delivery capable of charging larger USB devices like laptops.



Includes pre-installed solar charging optimization module that functions as a maximum power point tracker (MPPT), resulting in up to 40% faster charge times.




With LiFePO4 lithium cells, known for stability and safety, monitored by a state-of-the-art battery management system that prevents over-charge, over-current, and short circuiting.




Built in Multi safety protection that include short circuit, overload and over-temperature and error code reporting.



Camping



Office



Shop



Home

MODEL	HBP18-1212	HBP18-2024	HBP18-3024			
<b>INVERTER</b>						
Rated power	1200W	2000W	3000W			
Surge power	2400W	4000W	6000W			
Output voltage waveform		Pure sine wave				
Output voltage regulation		220~240Vac(setting)				
Output frequency		50Hz / 60Hz (±0.2Hz)				
Peak efficiency		90~93%				
Nominal DC input voltage	12Vdc (±0.3)	24Vdc (±0.3)	24Vdc (±0.3)			
Standby Consumption		< 25W				
<b>PV INPUT</b>						
Max solar power input	900W	1800W	1800W			
PV max charging current	60A (±3A)	60A (±3A)	60A (±3A)			
Combined charging current	70A (±4A)	80A (±4A)	80A (±4A)			
Max efficiency		98.0% max				
PV array open circuit voltage	105VDC	160VDC	160VDC			
PV Array MPPT Voltage Range	15~105V	30~128VDC	30~128VDC			
<b>AC INPUT</b>						
AC input voltage		230Vac ±5%				
Acceptable input voltage range		90-280VAC				
Nominal input frequency		50Hz / 60Hz (Auto detection)				
Transfer time		10ms typical (UPS, VDE); 20ms typical (APL)				
<b>AC CHARGE</b>						
Charging current @ Nominal input voltage	10A (±4A)	20A/(±4A)	60A (±4A)			
Charging Algorithm		4-step (Li)				
<b>OUTPUT</b>						
AC output		230Vac (Socket *4pcs)				
Type-C		DC output*1pcs				
USB (5V 2.4A)		DC output*4pcs				
USB (12V 1A)		DC output*2pcs				
<b>LITHIUM BATTERY</b>						
Energy	1280Wh	2560Wh	3072Wh	7168Wh		
Nominal voltage	12.8V	25.6V		25.6V		
Battery capacity	100Ah	100Ah	120Ah	280Ah		
Protection board	100A	100A		150A		
Standard charging & discharge current	50A	50A	50A	50A		
Operating temperature	Charge	0~45°C				
	Discharge	-10~60°C				
<b>DIMENSION</b>						
Machine Dimension (W*H*D)(mm)		359*499*234	420*497*280	460*539*411		
Package Dimension (W*H*D)(mm)		460*560*335	522*655*382	570*702*521		
N.W(kg)	21	30	36	66		
G.W(kg)	26	41	45	80		
Standard Warranty	Inverter: 2 years ; Lithium battery: 3 years					
<b>CERTIFICATION &amp; STANDARDS</b>						
CE-EMC+LVD (EN6100-6-3, EN6100-6-1+EN IEC62109-1, EN IEC62109-2); IEC62368-1						

\*The technical specifications of this document are subject to change without any notice