

Model: LINKFLOOR ECO DYNASTY LIGHT

Codes: 100354579

Group: G-242

Format: 20X181,5X0,9CM



COMPOSITION



	Size	Material	Type of material
Layer 1		Coating	Corundum protective wear layer
Layer 2		Digital print	Decorative layer with digital printing
Layer 3	1	Comfort Layer	Renewable raw materials layer
Layer 4	6.8	Waterproof base	Natural wood fiber base
Layer 5	1.2	Cork	Cork sheet

ADDITIONAL NOTES

Highly natural and sustainable product, manufactured without the use of plasticizers. The different layers that form the structure of each piece are made of renewable products such as wood, cork, rubber and other natural fibers.

FEATURES

-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
-  Is suitable for installing on water radiant heating
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  There are consistent color changes between pieces.
-  25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
-  5-year warranty on installations for residential use in models cataloged as suitable for bathrooms and kitchens.
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.



LABORATORY TESTS

Commercial area class	33	EN 16511*
Slip resistance (shod feet)	R-10	EN 16165 Anexo B*
Abrasion resistance	AC5	EN 13329 EN 15468*
Impact resistance	1500 mm/40 N	EN 438-2*
Resistance to staining	Grado 4-5	ISO 438-2*
Castor chair effect	WITHOUT VISIBLE EFFECTS	EN 425*
Dimensional stability	<0.05%	EN 434*
Resistance to microscratching	MSR-A1/MSR-B1	EN 16094*
Slip resistance (wet pendulum) irhd 55	CL 1 (31)	EN 16165 Anexo C*
Fire resistance	Cfl-s1	EN 13501-1*
Heat resistance	0.07 M2*K/W	EN 12667*
Thermal conductivity	0.118 W/M*K	EN 12667*
Uv light fastness	>7	ISO 105-B02*
Acoustic insulation	ca. Lw=17 dB	ISO 10140*
Dynamic coefficient of friction (dcof)	0.58	ANSI 137.1*
Private area class	23	EN 16511*
Slip resistance (pendulum-dry)	90	EN 16165 Anexo C*

PACKING

Sales units per box	2.178 M2/BOX	
Sales units per pallet	121.968 M2/PAL	
Sales units per unit	0.363 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Sales units per square meter	1 M2	
Net weight	7.548209 KG/M2	
Gross weight	7.85124 KG/M2	

SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100355003	MAMPER LINK ECO DYNASTY LIGHT 7X120	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100354999	PERFIL ADH LINK ECO DYNASTY LIGHT 3,5	G-155							
100155425	ZOCALO LAMINADO BLANCO 8X220X1,5	G-110	14 PIECES/BOX	560 PIECES/PAL	5.68 PIECES/M2	-	-	1.89 KG/PIECES	1.98 KG/PIECES

