

Model: LINKFLOOR TOWN BEIGE

Codes: 100380124

Group: G-222

Format: 22,8X180X0,55CM



COMPOSITION



	Size	Material	Type of material
Layer 1	0.5	Wear layer	Use layer with PU protection
Layer 2	0.1	Vinyl	
Layer 3	3.9	SPC	SPC core
Layer 4	1.0	IXPE	Foam

CERTIFICATIONS

Floorscore certification

SCS-FS-20327

FEATURES

-  Imitates the surface of wood
-  Water and moisture resistant flooring, suitable for wet areas such as bathrooms and kitchens for residential use, provided the product's installation instructions are followed.
-  5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  There are consistent color changes between pieces.
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
-  Is suitable for installing on water radiant heating
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



LABORATORY TESTS

Commercial area class	33	EN 10582**
Slip resistance (shod feet)	R10	EN 16165 Anexo B*
Abrasion resistance	CLASS T	EN 660-2:199+A1 2003 / EN 649:2011*
Resistance to staining	CLASS 0	ISO 26987*
Resistance to microscratching	MSR-A1/MSR-B1	EN 16094*
Formaldehyde emissions	E1	EN 717-2*
Slip resistance (wet pendulum) irhd 55	CL 2 (38)	EN 16165 Anexo C*
Tensile strength of joints	6.56 kN/m	ISO 24334*
Fire resistance	Bfl-s1	EN 14041:2004 AC:2006*
Fire resistance	CLASS A	ASTM E84*
Evaluation of propensity to accumulation of electrostatic charges	1.13 KV	EN 1815*
Heat resistance	0.049 M2*K/W	EN 12664*
Thermal conductivity	0.113 W/M*K	EN 12664*
Uv light fastness	≥6	EN ISO 105 B02:1999+A1:2002*
Acoustic insulation	(8"): IIC=58 dB; STC=54 dB	ASTM E492 ; ASTM E90*
Acoustic insulation	Rw=55 dB; Ln,w=57 dB	EN ISO 717-1*
Acoustic insulation	ΔLw=21 dB	EN ISO 717-2*
Dynamic coefficient of friction (dcof)	0.49	ANSI 137.1*
Smoke density (burning)	SDI: 400	ASTM E84*
Private area class	23	EN 10582**
Slip resistance (pendulum-dry)	86	EN 16165 Anexo C*

PACKING

Sales units per box	2.4624 M2/BOX	
Sales units per pallet	108.3456 M2/PAL	
Sales units per unit	0.4104 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Sales units per square meter	1 M2	
Net weight	9.943957 KG/M2	
Gross weight	10.3923 KG/M2	

SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100354777	MAMPER LINKFLOOR TOWN BEIGE 7X120	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100364997	PERF. ADH. LINKFLOOR TOWN BEIGE4X250X0,3	G-155	30 PIECES/BOX	3000 PIECES/PAL	10 PIECES/M2	-	-	0.7 KG/PIECES	0.72 KG/PIECES
100257147	PERFIL ADH LINKFLOOR ALUMINIO 3,5X270	G-121	40 PIECES/BOX	1000 PIECES/PAL	10.58 PIECES/M2	-	-	0.37 KG/PIECES	0.39 KG/PIECES
100354769	ZOCALO LINKFLOOR PVC TOWN BEIGE 8X223	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	-	1.1 KG/PIECES	1.25 KG/PIECES
100343146	ZOCALO PVC PAPEL BLANCO 8X223X1,5	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	-	1.41 KG/PIECES	1.49 KG/PIECES

