

Model: AC6 NATURAL 1L YUKON

Codes: 100244121

Group: G-213

Format: 19,3X128,2X0,8CM



COMPOSITION



	Size	Material	Type of material
Layer 1		Melamine	Aminoplastic thermosetting resins
Layer 2		Decorative paper	
Layer 3	7,5	HDF	
Layer 4	0.1	Backside	Sheets of kraft paper impregnated with phenolic resins

FEATURES

-  Imitates the surface of wood
-  Gloss-free
-  25 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Is suitable for installing on water radiant heating
-  Environmental Product Declarations for Construction (DAPcons®) are an essential instrument for environmental improvement in the construction sector and, therefore, a useful tool for technicians, manufacturers and users. DAPcons® certifications cover products from the different stages of a building. They provide objective, agreed and verified information on a product.
-  It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly
-  33. Intensive commercial
-  Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.
-  Beveled cut on all 4 edges of the board for emphasizing size
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  5-year warranty on installations for residential use in models cataloged as suitable for bathrooms and kitchens.
-  Format where only one board has been used to finish the entire base surface
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  23. Intensive residential
-  AC6 Abrasion resistance level according to UNE-EN 13329.



DIMENSIONAL FEATURES

Item thickness	≤0.50 mm	EN 13329*
Length of face	0.50 mm	EN 13329*
Width of face	Δ medios≤0.10 medio/máx-mins≤0.20 mm	EN 13329*
Squareness of the item (q)	≤0.20 mm	EN 13329*
Straightness of face	≤0.30 mm/M	EN 13329*
Flatness of item (f)	fw cóncavos≤0.15/fw convexos≤0.20/fl cóncavos≤0.50/fl convexos≤1.00 %	EN 13329*
Joint between items	medios≤0.15/máx≤0.20 mm	EN 13329*
Difference in height among items	Max≤0.15/Proms≤0.10 mm	EN 13329*
Dimensional variations related to changes in relative moisture	medios≤0.9 mm	EN 13329*
Uv light fastness	escala azul: no inferior categoría 6-Escala gris: No inferior a categoría 4	EN 438-2,16*
Surface stripping	≥1.25 N/mm2	EN 13329 Anexo D*

LABORATORY TESTS

Resistance to abrasion	AC6	UNE EN 13329:2000*
Impact resistance	≥1000 mm/≥15 N	EN 13329*
Resistance to staining	Grado 5 (G 1 y 2) y Grado 4 (G 3)	EN 438-2*
Swelling in thickness	≤8%	EN 13329*
Moisture upon leaving factory	4-10 %	
Resistance to microscratching	Clase 1	EN 16094*
Formaldehyde emissions	E1≤0.05 ppm	DIN EN 717-1*
Slip resistance (wet pendulum) irhd 55	CL 1 (29)	EN 16165 Anexo C*
Tensile strength of joints	≥1kN/m	EN 13329*
Fire resistance	Cfl-S1	DIN EN 13501-1*
Evaluation of propensity to accumulation of electrostatic charges	≤2 KV	EN 1815*
Heat resistance	0.065 M2*K/W	
Thermal conductivity	0.123 W/M*K	
Dynamic coefficient of friction (dcof)	0.60	ANSI A137.1*
Density of the board	901 kg/m3-7.21 kg/m2	EN 323*
Slip resistance (pendulum-dry)	CL 2 (42)	EN 16165 Anexo C*
Slip resistance (shod feet)	R-9	EN 16165 Anexo B*
Topical moisture resistance	Qualitatives≤2/cuantitatives≤0.3 mm	ISO 4760*

PACKING

Sales units per box	1.979408 M2/BOX	
Sales units per pallet	102.929215 M2/PAL	
Sales units per unit	0.247426 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Sales units per square meter	1 M2	
Net weight	8.014518 KG/M2	
Gross weight	8.228723 KG/M2	

SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100228951	IGUALACION NATURAL 1L YUKON 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.7 KG/PIECES	0.72 KG/PIECES
100228976	MAMPERLAN AC6 NATURAL 1L YUKON 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100228964	TRANSICION NATURAL 1L YUKON 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.7 KG/PIECES	0.72 KG/PIECES
100228922	ZOCALO NATURAL 1L YUKON 8X220X1,5	G-107	14 PIECES/BOX	560 PIECES/PAL	5.68 PIECES/M2	-	-	1.8 KG/PIECES	1.86 KG/PIECES

