

Technical sheet :

TILTING FORKS CARRIAGE



Customer benefits

- Efficient handling solution.
- Adapted to rough terrain.

Technical characteristics

- Tilting forks.
- Forks compliant with FEM/ISO standard, forks' length according to model.
- Forks are not included in the PFB, order 2 forks (except for CAT 1020 / 1500 + 2 F 100x40x1200 & CAT 1260 / 5T + F 150x50x1200 reference).

[The 3D picture at the top of this page is the reference CAT 1020 / 1500 + 2 F 100x40x1200 - 52706271].

Capacities		CAT 1020 / 1500 + 2 F 100x40x1200	CAT 1260 / 5 T + F 150x50x1200	PFB 20N 1020	PFB 25N 1020	PFB 25N 1260	PFB 35N 1260	PFB 35N 1470	PFB 35N 1580	PFB 45N 1260	PFB 45N 1670
Capacity (kg)		1500	5000	2000	2500	2500	3500	3500	3500	4500	4500
Weight											
Overall weight (kg)		137	406	166	71	80	93	117	122	198	252
Weight and dimensions											
Overall height (mm)	h17	695	677	582	-	-	-	-	-	-	-
Overall length (mm)	l1	1372	1497	-	-	-	-	-	-	-	-
Width (mm)		1052	1302	1052	1026	1302	1302	1512	1622	1286	1696
Working Parameters											
Required machine equipment		✕	✕	✕	✕	✕	✕	✕	✕	✕	✕
Minimum forks spread (mm)	b5	201	306	216	-	-	-	-	-	-	-
Maximum forks spread (mm)	b5	965	1150	980	-	-	-	-	-	-	-
Available fork dimensions											
100 x 40 x 1200		53016603		415691							
125 x 45 x 1200					415835		415618				
125 x 50 x 1200										415652	
150 x 50 x 1200			578097								

Machines compatibility		CAT 1020 / 1500 + 2 F 100x40x1200	CAT 1260 / 5 T + F 150x50x1200	PFB 20N 1020	PFB 25N 1020	PFB 25N 1260	PFB 35N 1260	PFB 35N 1470	PFB 35N 1580	PFB 45N 1260	PFB 45N 1670
Reference number		-	52735505	52000814	571958	571959	653744	653745	653746	654407	653747
Skid Steer Carriage reference		-	-	-	52000825	-	-	-	-	-	-
All-Tach®		52706271	-	-	-	-	-	-	-	-	-
4 point Carriage		52723636	-	-	-	-	-	-	-	-	-
Euro Carriage		52723637	-	-	-	-	-	-	-	-	-
ALT950		-	-	-	-	-	X	-	-	-	-
GCT 3-14		X	-	-	-	-	-	-	-	-	-
GCT 3-14 +		X	-	-	-	-	-	-	-	-	-
MLA-T 533-145 V+ - ST5		-	-	-	-	-	X	-	-	-	-
MLT 420-60 H		-	-	X	-	-	-	-	-	-	-
MLT 625-75 H		-	-	-	X	X	-	-	-	-	-
MLT 630-115		-	-	-	-	-	X	X	X	-	-
MLT 630-115 V		-	-	-	-	-	X	X	X	-	-
MLT 630-115 V CP		-	-	-	-	-	X	X	X	-	-
MLT 635-130 PS+		-	-	-	-	-	X	X	X	-	-
MLT 635-140 V+		-	-	-	-	-	X	X	X	-	-
MLT 730-115 V		-	-	-	-	-	X	X	X	-	-
MLT 730-115 V CP		-	-	-	-	-	X	X	X	-	-
MLT 733-115		-	-	-	-	-	X	X	X	-	-
MLT 738-130 PS+		-	-	-	-	-	-	-	-	X	X
MLT 742-130 PS+		-	-	-	-	-	-	-	-	X	X
MLT 742-140 V+		-	-	-	-	-	-	-	-	X	X
MLT 841-145 PS+		-	-	-	-	-	-	-	-	X	X
MLT 850-145 V+		-	X	-	-	-	-	-	-	-	-
MLT 937-115		-	-	-	-	-	-	-	-	X	X
MLT 940-140 V+		-	-	-	-	-	-	-	-	X	X
MLT 1041-145 PS+L		-	-	-	-	-	-	-	-	X	X
MLTX 625-75 H		-	-	-	X	X	-	-	-	-	-
MLTX 732		-	-	-	-	-	X	-	-	-	-
MLTX 735 T LSU		-	-	-	-	-	X	X	X	-	-
MLTX 738-130 PS+		-	-	-	-	-	-	-	-	X	X
MLTX 741 T LSU		-	-	-	-	-	-	-	-	X	X
MLTX 841 - 145 PS+		-	-	-	-	-	-	-	-	X	X
MLTX 850-145 V+		-	X	-	-	-	-	-	-	-	-
MLTX 1041-145 PS+L		-	-	-	-	-	-	-	-	X	X
MT 420 H		-	-	X	-	-	-	-	-	-	-
MT 625 H		-	-	-	X	X	-	-	-	-	-
MT 625 H Comfort		-	-	-	X	X	-	-	-	-	-
MT 625 HA		-	-	-	X	X	-	-	-	-	-
MT 735 75D ST5		-	-	-	-	-	X	X	X	-	-
MT 935 75D ST5		-	-	-	-	-	X	X	X	-	-
MT 1135 75 D		-	-	-	-	-	X	X	X	-	-
MT 1135 H 100D		-	-	-	-	-	X	X	X	-	-
MT 1335 75D ST5		-	-	-	-	-	X	X	X	-	-
MT 1335 100D ST5		-	-	-	-	-	X	X	X	-	-
MT 1335 H 75D ST5		-	-	-	-	-	X	X	X	-	-
MT 1335 H 100D ST5		-	-	-	-	-	X	X	X	-	-
MT 1335 HA 75D ST5		-	-	-	-	-	X	X	X	-	-
MT 1335 HA 100D ST5		-	-	-	-	-	X	X	X	-	-
MT 1440 A ST5		-	-	-	-	-	-	-	-	X	-
MT 1440 easy ST5		-	-	-	-	-	-	-	-	X	-
MT 1440 HA ST5		-	-	-	-	-	-	-	-	X	-
MT 1440 ST5		-	-	-	-	-	-	-	-	X	-
MT 1840 A 100D ST5 S1		-	-	-	-	-	-	-	-	X	-
MT 1840 easy ST5		-	-	-	-	-	-	-	-	X	-
MT 1840 HA		-	-	-	-	-	-	-	-	X	-
MT 1840 ST5		-	-	-	-	-	-	-	-	X	-
MTX 420 H		-	-	X	-	-	-	-	-	-	-
MTX 733 Mining		-	-	-	-	-	X	X	X	-	-

Machines compatibility	CAT 1020 / 1500 + 2 F 100x40x1200	CAT 1260 / 5 T + F 150x50x1200	PFB 20N 1020	PFB 25N 1020	PFB 25N 1260	PFB 35N 1260	PFB 35N 1470	PFB 35N 1580	PFB 45N 1260	PFB 45N 1670
MTX 735	-	-	-	-	-	X	X	X	-	-
MTX 1033 Mining	-	-	-	-	-	X	X	X	-	-
MTX 1033 A Mining	-	-	-	-	-	X	X	X	-	-
MTX 1135	-	-	-	-	-	X	X	X	-	-
MTX 1440	-	-	-	-	-	-	-	-	X	X
MTX 1440 A	-	-	-	-	-	-	-	-	X	X
MTX 1840	-	-	-	-	-	-	-	-	X	X
MTX 1840 A	-	-	-	-	-	-	-	-	X	X
ULM 412 H	X	-	-	-	-	-	-	-	-	-
ULM 412 H	X	-	-	-	-	-	-	-	-	-
ULM 415 H	X	-	-	-	-	-	-	-	-	-
ULM 415 H	X	-	-	-	-	-	-	-	-	-
MLT 630-105 ST4 OLD	-	-	-	-	-	X	X	X	-	-
MLT 630-105 V CP ST4 OLD	-	-	-	-	-	X	X	X	-	-
MLT 630-105 V ST4 OLD	-	-	-	-	-	X	X	X	-	-
MLT 630-115 OLD	-	-	-	-	-	-	X	X	-	-
MLT 630-115 V OLD	-	-	-	-	-	X	X	X	-	-
MLT 630-115 V CP OLD	-	-	-	-	-	X	X	X	-	-
MLT 635-130 PS+ OLD	-	-	-	-	-	X	X	X	-	-
MLT 635-130 PS+ ST4 OLD	-	-	-	-	-	X	X	X	-	-
MLT 635-140 V+ OLD	-	-	-	-	-	X	X	X	-	-
MLT 635-140 V+ ST4 OLD	-	-	-	-	-	X	X	X	-	-
MLT 730-115 V OLD	-	-	-	-	-	X	X	X	-	-
MLT 730-115 V CP OLD	-	-	-	-	-	X	X	X	-	-
MLT 730-115 V CP ST4 OLD	-	-	-	-	-	X	X	X	-	-
MLT 730-115 V ST4 OLD	-	-	-	-	-	X	X	X	-	-
MLT 733-115 OLD	-	-	-	-	-	X	X	X	-	-
MLT 733-115 LSU OLD	-	-	-	-	-	X	X	X	-	-
MLT 733-115 LSU ST4 OLD	-	-	-	-	-	X	X	X	-	-
MLT 733-115 ST4 OLD	-	-	-	-	-	X	X	X	-	-
MLT 737-130 PS+ OLD	-	-	-	-	-	-	-	-	-	X
MLT 737-130 PS+ ST4 OLD	-	-	-	-	-	-	-	-	X	X
MLT 741-130 PS+ OLD	-	-	-	-	-	-	-	-	X	X
MLT 741-140 V+ OLD	-	-	-	-	-	-	-	-	X	X
MLT 741-140 V+ ST4 OLD	-	-	-	-	-	-	-	-	X	X
MLT 840-145 PS+ OLD	-	-	-	-	-	-	-	-	X	X
MLT 845-100 H OLD	-	-	-	-	-	-	-	-	X	X
MLT 845-120 OLD	-	-	-	-	-	-	-	-	X	X
MLT 940-140 V+ OLD	-	-	-	-	-	-	-	-	-	X
MLT 940-140 V+ ST4 OLD	-	-	-	-	-	-	-	-	X	X
MLT 1040-145 PS+ L OLD	-	-	-	-	-	-	-	-	X	X
MLT-X 737-130 PS+ OLD	-	-	-	-	-	-	-	-	X	X
MLT-X 737-130 PS+ OLD	-	-	-	-	-	-	-	-	-	X
MLT-X 741-140 V+ S1 OLD	-	-	-	-	-	-	-	-	X	X
MLT-X 840-140 PS+ OLD	-	-	-	-	-	-	-	-	X	X
MLT-X 1035 LT LSU OLD	-	-	-	-	-	X	X	X	-	-
MLT-X 1040-140 PS+ L OLD	-	-	-	-	-	-	-	-	X	X
MT 733 Easy OLD	-	-	-	-	-	X	X	X	-	-
MT 933 Easy OLD	-	-	-	-	-	X	X	X	-	-
MT 1033 easy OLD	-	-	-	-	-	X	X	X	-	-
MT 1135 OLD	-	-	-	-	-	X	X	-	-	-
MT 1335 OLD	-	-	-	-	-	X	X	-	-	-
MT 1440 OLD	-	-	-	-	-	-	-	-	X	X
MT 1840 OLD	-	-	-	-	-	-	-	-	X	X
MT 1840 HA OLD	-	-	-	-	-	-	-	-	X	-

Capacities		PFB 4SN 2000	PFB 75MT 1750	PFB 75MT 2000	PFB FEM4 1200
Capacity (kg)		4500	7500	7500	6000
Weight					
Overall weight (kg)		295	-	-	-
Weight and dimensions					
Overall height (mm)	h17	-	-	-	-
Overall length (mm)	l1	-	-	-	-
Width (mm)		2026	1834	2084	1200
Working Parameters					
Required machine equipment		✕	✕	✕	✕
Minimum forks spread (mm)	b5	-	-	-	-
Maximum forks spread (mm)	b5	-	-	-	-
Available fork dimensions					
125 x 50 x 1200		615652			
200 x 60 x 1200					513110

Machines compatibility	PFB 4SN 2000	PFB 75MT 1750	PFB 75MT 2000	PFB FEM4 1200
Reference number	653748	504107	527216	732330
Skid Steer Camage reference	-	-	-	-
All-Tach®	-	-	-	-
4 point Camage	-	-	-	-
Euro Camage	-	-	-	-
MLT 738-130 PS+	X	-	-	-
MLT 742-130 PS+	X	-	-	-
MLT 742-140 V+	X	-	-	-
MLT 937-115	X	-	-	-
MLT 940-140 V+	X	-	-	-
MLT 961-160 V+ L	-	X	X	X
MLT-X 738-130 PS+	X	-	-	-
MLT-X 961-160 V+ L	-	X	X	X
MT 1440 A ST5	X	-	-	-
MT 1440 easy ST5	X	-	-	-
MT 1440 HA ST5	X	-	-	-
MT 1440 ST5	X	-	-	-
MT 1840 A 100D ST5 S1	X	-	-	-
MT 1840 easy ST5	X	-	-	-
MT 1840 HA	X	-	-	-
MT 1840 ST5	X	-	-	-
MT-X 1440	X	-	-	-
MT-X 1440 A	X	-	-	-
MT-X 1840	X	-	-	-
MT-X 1840 A	X	-	-	-
MLT 737-130 PS+ OLD	X	-	-	-
MLT 737-130 PS+ ST4 OLD	X	-	-	-
MLT 741-130 PS+ OLD	X	-	-	-
MLT 741-140 V+ OLD	X	-	-	-
MLT 741-140 V+ ST4 OLD	X	-	-	-
MLT 845-100 H OLD	X	-	-	-
MLT 845-120 OLD	X	-	-	-
MLT 940-140 V+ OLD	X	-	-	-
MLT 940-140 V+ ST4 OLD	X	-	-	-
MLT 961-145 V+ L OLD	-	X	X	X
MLT-X 737-130 PS+ OLD	X	-	-	-
MLT-X 737-130 PS+ OLD	X	-	-	-
MLT-X 741-140 V+ S1 OLD	X	-	-	-
MLT-X 845-120 OLD	X	-	-	-
MLT-X 845-120 H OLD	X	-	-	-
MLT-X 961-145 V+ L OLD	-	X	X	X
MT 1440 OLD	X	-	-	-
MT 1840 OLD	X	-	-	-
MT 1840 HA OLD	X	-	-	-

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes