

F Series Rotary Screw Air Compressors

The Tamsan-USA **F Series** Compressor sets a new industry standard with the Flip top service hood and *gas assist spring*. With the user in mind, this design allows for easy access to service parts for faster service time and less physical strain making it the easiest screw compressor to service. This rugged, quiet machine can go the distance. That is why we back the **F Series** compressor with our **lifetime airend warranty**.

General equipment information:

- 32psi adjustable minimum pressure check valve
- Normally closed, load-empty suction valve with command
- 2 micron resolution dry-type air filter
- 71 F controlled thermostatic valve
- Microglass front fiber air panel filter



For additional information about the compressor, scan the QR code.



MODEL	PRESSURE (PSIG)	FLOW (cfm)	MOTOR (HP / kW)		SOUND LEVEL (dB)	CONNECTION (INCH)	SIZES (INCH)	WEIGHT (LB)
TVK-7.5F	125	28	7.5	5.5	66	3/4"	29" x 39" x 44"	397
	145	23						
	195	19						
TVK-10F	125	38.8	10	7.5	66	3/4"	29" x 39" x 44"	541
	145	30						
	195	27.5						
TVK-15F	125	65.3	15	11	69	3/4"	32" x 50" x 49"	816
	145	56.5						
	195	49.4						
TVK-20F	125	85.5	20	15	68	1"	32" x 50" x 49"	926
	145	71						
	195	60						
TVK-25F	125	106.3	25	18.5	68	1"	35" x 52" x 52"	1048
	145	88.3						
	195	77.7						
TVK-30F	125	127.1	30	22	68	1"	35" x 52" x 52"	1070
	145	106.3						
	195	91.8						

Images are for illustrative purposes only. Actual models may vary based on size and configuration.