

# **FULLY SYNTHETIC**

Prolong Engine Life
Sludge and deposit protection

www.eneos.asia

**Product Data Sheet** 

### **DESCRIPTION**

ENEOS X Series brings the advanced technology and highest quality specification standards together in the premium engine oil especially formulated for the latest generation of cars. The new range in ENEOS product line meets the highest emission norms and fuel saving standards, extend engine lift through reduced sulphur content and helps preventing low-speed pre-ignition (LSPI) events.

## **ADVANTAGES**

#### ENEOS X SP/GF-6A 5W-30 offers:

- Outstanding anti-wear protection under a wide variety of driving conditions.
- · Protection against sludge, engine rust and corrosion under severe operating conditions.
- Improve engine efficiencies by reducing Engine Low Speed Pre-Ignition (LSPI)
- Extending performance and engine life by working to prevent damaging deposits and sludge build up.

#### PERFORMANCE LEVEL

SP/GF-6A CF Performance

### **APPLICABLE**

- Designed for modern gasoline-powered vehicles, including high-performance turbocharged and supercharged vehicles.
- Compatible with gasoline and diesel vehicles.
- All types of diesel engine where this viscosity is recommended.
- Recommended for cars made by world-leading manufacturers.
- Check user's manual for the manufacturer's recommended oil viscosity grade, API service classification.

# **CONTAINER SIZE**

200 Litre

## TYPICAL CHARACTERISTICS

SAE Grade			5W-30
API Performance Grade			SP
ILSAC			GF-6A
Density (15°C) g/cm³		ASTM D 4052	0.8506
Viscosity mm <sup>2</sup> /s	(40°C)	ASTM D 445	57.74
	(100°C)	ASTM D 445	9.736
Viscosity Index		ASTM D 2270	154
Flash Point °C		ASTM D 6749	212
Pour Point °C		ASTM D 97	-36
Base Number		ASTM D 2896	7.46

Note: Typical characteristics are subject to change without notice (Feb, 2023)

#### Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations