

L

U

M

AGRI

SINGLE-AXIS TRACKER

With **Luma** Agri “1P” formation, efficiency meets elegance with a single row of panels arranged in a portrait orientation. Its central axis gracefully aligns along the midpoint, ensuring optimal solar tracking performance.

TRACKER FEATURES



FIT FOR
AGRIVOLTAICS



NIGHT FLIP



OFF-SET
INSTALLATION



ADJUSTABLE
HEIGHT



ADJUSTABLE
ARRAY LENGTH



TRACKING

- Tracking Method Single-Axis, horizontal (N-S installation)
- Tracking Range -85° $+85^{\circ}$ [-90° , $+180^{\circ}$ With Night-Flip Mode]
- Backtracking Configurable to terrain
- Accuracy 0.1°

CONFIGURATION

- No. of Panels Up to 48 Modules per Array
- Tracker Layout 2 Arrays with 2 Sections each (up to 24 modules per Section)
- Tracker Unit 2 Arrays with 1 Controller
- Drive Type Slewing Drive with DC Motor
- Tracker per MWP Approx. 15 Trackers (30 Arrays)

Two arrays are mechanically independent, but each SolTrk controller manages 2 arrays

PERFORMANCE

- Capacity per tracker Up to 60kWp (Depending on Panel)
- DC Motor Operating Voltage 24V / DC
- Performance Temperature Range -40°C up to $+70^{\circ}\text{C}$

INSTALLATION TOLERANCES

- N-S Slope 6°
- Pole Height $\pm 25\text{mm}$
- Pole plumb $\pm 1^{\circ}$
- Pole Twist $\pm 2^{\circ}$

DIMENSIONS

- Length 62,5m / 205 ft
- Width 2.4 m / 7.9 ft
- Height 2.4 m / 7.9 ft

ADDITIONAL FEATURES

- Monitoring Real Time Documentation
- Over Current Protection Yes
- Motor Torque Control Yes
- Remote Control Yes
- Warranty Up to 20 Years

