



# TYPE SG & SGS TRAILED



## TYPE SG & SGS TRAILED

***A sand-/salt spreader that can also be used for spreading lime, compost, fertilizer etc.***

Bredal A/S has for many years produced lime and fertilizer spreaders for agriculture and its reputation all over the world can be summed up in three key words: *Simple, precise & reliable*. These 3 words have been the key objectives in developing all Bredal spreaders and this focus has continued in the development of the new SG model.

**Simple:** The spreader is developed in a way that ensures that daily use, settings and maintenance are made as simple as possible. This ensures accurate application rates and an exact spread pattern with less risk of error.

**Precise:** Using knowledge built up over the years in spreading a wide range of products including fertilizer, lime, top dressing and compost, Bredal has developed the SG spreader to accurately spread sand and salt for winter use, but also precisely spread fertilizer, lime or sand top dressing etc. out of the winter season.

**Reliable:** Due to the simple construction and the use of high quality components, Bredal has designed a machine with a long working life. The simple construction also ensures easy maintenance and less risk of down time.



# TYPE SG & SGS TRAILED



## Bredal SG:

- Simple
- Precise
- Reliable
- Professional spreader
- 2 disc spreader
- Precise Spreading over full width
- Positive Metering
- Versatile Spreading
- No agitators
- Easy in operation
- High capacity
- Solid construction

## TYPE SG & SGS TRAILED

SG-Series is available in 2 different versions

|                  | <b>SG-4500</b> | <b>SG-6500</b> |
|------------------|----------------|----------------|
| Hopper volume*:  | 3500 ltr       | 5000 ltr       |
| Hopper length*:  | 290 cm         | 300 cm         |
| Hopper width*:   | 195 cm         | 215 cm         |
| Loading height*: | 205 cm         | 230 cm         |
| Total length*:   | 530 cm         | 530 cm         |
| Total width*:    | 230 cm         | 252 cm         |
| Total weight*:   | 1600 kg        | 2000 kg        |
| Spreading width: | 2-10 m         | 2-10 m         |

*\*All info is for standard versions.*

**SG- version:** Is manually operated using 2 hyd. valves to regulate speed of the floorbelt and spread discs. Option for speed related application with a mechanical drive wheel.

**SGS- version:** Is controlled by the TeeJet500 computer, which allows the spreader to be adjusted from the tractor cab and application rate is forward speed related.

SGS & SG- versions require an oilflow of app. 30 ltr/min.

Possibility of buying various extra equipment.