

SENSIT[®] GOLD 2

MULTI GAS DETECTOR

FIELD-PROVEN GAS SAFETY

LOCATE ABOVE & BELOW GROUND LEAKS



Readings in
PPM, LEL,
and/or
%VOL

Methane &
Propane
Selectable

Audible/Visual
Alarms & Tick
Mode

Configurable
Up To 4 Gases

Replaceable
Alkaline
Batteries



METHANE GAS CONVERSION

% GAS	% LEL	PPM	% GAS	% LEL	PPM
-	0.1	50	2.0	40.0	20,000
-	0.2	100	2.5	50.0	25,000
-	1.0	500	3.0	60.0	30,000
0.1	2.0	1,000	3.5	70.0	35,000
0.5	10.0	5,000	4.0	80.0	40,000
1.0	20.0	10,000	4.5	90.0	45,000
1.5	30.0	15,000	5.0	100.0	50,000

ALARM PRESET THRESHOLDS

Combustible Gas Alarm	Preset for 50% LEL
Carbon Monoxide (CO)	Preset at 35 PPM
Oxygen (O2)	Preset at Below 19.5% & Above 23.5%
Hydrogen Sulfide (H2S)	Preset at 10 PPM
Hydrogen Cyanide (HCN)	Preset to PPM



LEL/PPM SENSOR

INFRARED COMMUNICATIONS

- | Download Calibration Data
- | Communicate with Smart-Cal

3 BUTTON OPERATION

A

- | Power On/Off
- | Mute
- | Smart-Cal Features
- | Exit Menu

B

- | Tick Control
- | Barhole
- | Test Modes
- | Select Menu Items

C

- | Data Save
- | Manually Zero Sensors
- | Change Menu Items

Learn more at gasleaksensors.com