

C400

For 2" to 6" PE Pipe

55 lbs / Height 21.5" / Width 16.25"

MODEL FEATURES

- Gear-drive mode delivers strong force with minimal effort, including heavy wall HDPE pipe
- Built from aircraft-grade aluminum, making it strong, lightweight, and easy to handle
- Standard gauge plate settings offer stops for the most common pipe diameters and SDRs
- Swing-out bottom bar design locks easily onto pipe while reducing overall trench profile



C400



The C400 incorporates all the features of the manual models, plus a unique worm gear drive, providing operator-friendly use and superior power delivery for larger diameter pipes. It features 6-sided, positive locking, indexable gauge plates, aircraft grade aluminum squeeze bars, chrome plated steel side shafts and a coated feed screw, reducing corrosion and friction.

This tool is operated with a right angle ratchet on the integral hex at the top of the feed screw. The unique swing-out/lock-in bottom bar design allows for quick and easy access to the pipe even in confined spaces, and the stabilizing bar provides added stability during the squeeze process.

Standard Gauge Plates

SIZE (DIAMETER)	SDR	SIZE (DIAMETER)	SDR
2"	11	4"	13.5
3"	11 & 11.5	6"	11 & 11.5
3"	13.5	6"	13.5
4"	11 & 11.5	6"	21
WEIGHT	SQUEEZE CAPACITY	HEIGHT	WIDTH
55 lbs (24.9 kgs)	2" - 6"	21.5" (29.5" Open)	16.25"

ADDRESS

1-54 Audia Crt. Vaughan, ON
Canada L4K 3N4

PHONE

Toll-Free: 1-888-737-3668
Local Area: +1-905-695-9900

EMAIL

sales@footage.ca