

C600

For 2" to 6" PE Pipe

75 lbs / Height 20" / Width 19"

MODEL FEATURES

- Designed to squeeze 2" to 6" MDPE and HDPE pipe safely and effectively
- Built from aircraft-grade aluminum, making it strong, lightweight, and easy to handle
- Standard gauge plate settings offer stops for the most common pipe diameters and SDRs
- Swing-out bottom bar design locks easily onto pipe while reducing overall trench profile



C600



The C600 features 8-sided, positive locking, indexable gauge plates, aircraft grade aluminum squeeze bars, chrome plated steel side shafts and a 10,000 PSI hydraulic system with quick connect fittings.

This CNC machined tool contains no welded parts and exerts 63,820 lbs of squeezing force. The unique lock-in / swing-out bottom bar design allows for quick and easy access to the pipe, even in confined spaces, and the lock down bolts ensure that a squeeze is maintained even if the hydraulics are disconnected.

The C600 also features flat squeeze bars with rounded edges to obtain maximum flow control with minimum pipe compression.

SIZE (DIAMETER)	SDR	SIZE (DIAMETER)	SDR
2"	11	4"	13.5
3"	11 & 11.5	6"	11 & 11.5
3"	13.5	6"	13.5
4"	11 & 11.5	6"	13.5
WEIGHT	SQUEEZE CAPACITY	HEIGHT	WIDTH
75 lbs (34 kg)	2" – 6"	29"	19"

ADDRESS

1-54 Audia Crt. Vaughan, ON
Canada L4K 3N4

PHONE

Toll-Free: 1-888-737-3668
Local Area: +1-905-695-9900

EMAIL

sales@footage.ca