

C100

For 1/2" to 2" PE Pipe

9.5 lbs / Height 12" / Width 6.75"

MODEL FEATURES

- Trusted by operators globally for daily squeeze off operations
- Lightweight design with aircraft-grade aluminum for easy handling and strength
- Features 6-sided indexable gauge plates for secure and precise operation
- Operates with a detachable torque bar or standard ratchet on the feed screw hex
- Swing-out/lock-in bottom bar enables quick set up in tight spaces



C100



The C100 features 6-sided, positive locking, indexable gauge plates, aircraft grade aluminum squeeze bars, chrome plated steel side shafts and a coated feed screw, reducing corrosion and friction.

The C100 can be operated with the detachable torque bar or with a ratchet on the integral hex at the top of the feed screw. The unique swing-out / lock-in bottom bar design allows for quick and easy access to the pipe even in confined spaces. The detachable stabilizing bar provides added stability during the squeeze process.

The C100 also includes a static grounding spike. Custom gauge plates are available upon request.

Standard Gauge Plates

SIZE (DIAMETER)	SDR	SIZE (DIAMETER)	SDR
1/2" CTS	7 (0.090 Wall)	1-1/4" IPS	10
1" CTS	11 (0.099) / 11.5 (0.101)	1-1/2" IPS	11
3/4" IPS	11	2" IPS	11
1" IPS	11		
WEIGHT	SQUEEZE CAPACITY	HEIGHT	WIDTH
9.5 lbs (4.3 kgs)	1/2" - 2"	12" (15" Open)	6.75"

ADDRESS

1-54 Audia Crt. Vaughan, ON
Canada L4K 3N4

PHONE

Toll-Free: 1-888-737-3668
Local Area: +1-905-695-9900

EMAIL

sales@footage.ca