

Parrot

ANAFI UKR

For covert ISR missions



GNSS-Denied Flight & Navigation



Multi-Connectivity*

MARS Military radio
LoRa
5G
Wi-Fi
Starlink

*Version dependant



Electronic Warfare resilience



Camera Module

35x
Zoom



FLIR BOSON 640
Thermal Camera

Ultra low acoustic signature

77_{dB}



Cursor On Target



48° 52' 47.276" N
2° 22' 4.806" E



Recognition & Tracking
Includes MGRS


FreeFlight 8



Software Included



ANAFI UKR Simulator



Map generators

Remote Antenna*



*Requires additional SKYCONTROLLER UKR

Cybersecurity by default



Open Source SDK Extensive Solutions Ecosystem



TECHNICAL SPECIFICATIONS

AIRCRAFT

- Size folded: 245 x 160 x 116 mm (9.6 x 6.3 x 4.6")
- Size unfolded: 350 x 665 x 116 mm (13.8 x 26.2 x 4.6")
- Mass: 959 g (2.11 lb)
- Maximum take-off mass (MTOM): 1,450 g / 3.20 lb
- Maximum transmission range:
 - MARS Radio*: 15 km / 9.32 mi
 - LoRa: 20 km / 12.43 mi
 - 5G*: range without limits
 - Wi-Fi*: 5 km / 3.1 mi
- Maximum flight time: 38 min at 6 m/s airspeed
- Maximum flight distance: 23.1 km (14.35 mi) at 10 m/s airspeed
- Maximum horizontal airspeed: 17 m/s
- Maximum horizontal groundspeed: 12.6 m/s
- Maximum ascent speed: 8 m/s
- Maximum descent speed: 8 m/s
- Maximum wind resistance:
 - During flight: 15 m/s
 - During take-off and landing: 15 m/s
- Maximum propeller speed: 8,500 rpm
- Sound power level at 1 m (3 ft): 77 dBA
- Service ceiling: 5,000 m above MSL (Mean Sea Level)
- Operating temperature: -36 °C to +50 °C (-33 °F to +122 °F)
- No take-off temperature limitation if battery is maintained between -20 °C and +50 °C (-4 °F to +122 °F)
- IP53: rain and dust resistant
- No NFZ (No-Fly Zones) limitation
- Takes off from / lands in the hand of the operator
- Full capability in GNSS-Denied flight conditions
- Indoor flight
- MicroSD card slot
- Deployment time: < 2 min

SENSORS

- Satellite navigation: GPS, GLONASS, Galileo & BeiDou
- Barometer and magnetometer
- Front and stereo cameras, and vertical range sensor
- 4 x 6-axis IMU (3-axis accelerometers + 3-axis gyroscopes) (Flight IMU: ICM-40609-D)

CYBERSECURITY

- Zero data shared without user consent
- Manage your data privately between drone and device or share anonymous data on secured European servers
- SD card AES-XTS encryption with a 512-bit key
- Digitally signed firmware
- Compliant with FIPS140-2

RADIO LINK

- MARS* (Radio-jamming resistance through Frequency Hopping)
- Encrypted backup LoRa radio
- 5G*
- Wi-Fi*
- Direct video stream resolution: 1080p at 30 fps
- AES 256 encryption: packet and radio level

EO IMAGE CHAIN

- 2 sensors: 1/2.4"
- Digital zoom: 35x
- Electronic shutter speed: 1/25 s to 1/10,000 s
- ISO range: 100 - 3,200
- Video resolution: 4K / FHD / HD
- Video format: MP4 (H.264 & H.265)
- Photo resolutions:
 - Wide: 21 MP (84° FOV)
 - Rectilinear: up to 16 MP (up to 75.2° FOV)
- Photo formats: JPEG, DNG (Digital Negative RAW)

IR IMAGE CHAIN

Sensor: FLIR BOSON

- Resolution: 640 x 512 px
- Temperature range: -40 °C to +250 °C (-40 °F to +482 °F)
- Thermal sensitivity: ≤60 mK
- Measured IR wavelength range: 8 to 14 micrometers
- Video resolution: UHD (2160p) at 8.6 fps
- Video format: MP4 (H.264 / H.265)
- Photo formats: JPEG

*Version Dependant

IMAGE STABILIZATION

- 3-camera IR/EO stabilized gimbal:
 - Hybrid: 3-axis
 - Mechanical: 3-axis
 - Electronics (EIS): 3-axis
- Controllable gimbal tilt range: -90° to +90°

SMART BATTERY

- Size: 136 x 73 x 46 mm (5.4 x 2.9 x 1.8")
- Mass: 344 g / 0.76 lb
- Type: High density LiPo (227 Wh/kg)
- Capacity: 6,800 mAh
- Voltage (nominal): 11.55 V (3 x 3.85 V cells)
- Charging port: USB-C
- Charges fully in 2 h 30 min with the USB-PD (Power Delivery) charger included in the pack
- Maximum charging power: 45 W

GROUND CONTROL STATION - PARROT SKYCONTROLLER UKR

- Size folded: 171 x 302 x 77 mm (6.7 x 11.9 x 3.0")
- Size unfolded: 171 x 302 x 215 mm (6.7 x 11.9 x 8.5")
- Mass: 1,764 g (3.89 lb)
- Battery capacity: 10,000 mAh
- Battery voltage (nominal): 7.2 V
- Battery charging duration: 2 h (2 h 30 min with tablet)
- Autonomy: 4 h 30 min
- Ports: USB-C (tablet), USB-C (charging), USB-A (pairing + accessory interface), Ethernet (Remote Antenna feature), HDMI
- IP53: rain and dust resistant
- ANAFI UKR is supplied with a Samsung tablet, but is also compatible with an iPad Mini.
- The system is also available without a tablet



Scan to
learn more