in

alentine.ch

THE CORE 400(T) TECHNICAL DATA SHEET



Technical data

CORE400	CORE400T
8540	8545
15-18 litres	15-18 litres
400x600x850/900	400x600x850/900
158x285x135	158x285x135
38-46kg/h	46-54kg/h
3N400V	3N400V
14.4 kW	18 kW
20A	26A
2	2
95°C – 190°C	95°C – 190°C
IPX4	IPX4
63kg	63kg
2.5m	2.5m
Supplied without plug	Supplied without plug
	8540 15-18 litres 400x600x850/900 158x285x135 38-46kg/h 3N400V 14.4 kW 20A 2 95°C - 190°C IPX4 63kg 2.5m Supplied without













THE CORE 400(T) TECHNICAL DATA SHEET



Features and benefits

- · Electromechanical thermostat
- · Temperature control knob
- · Integrated Sicotronic interface
- Intelligent adjustment for optimized performance and precise temperature control.
- Maximum insulation to optimize efficiency and heat retention, with minimal energy loss.
- · Fry tank with a cold zone for waste collection below the heating element, slowing down oil degradation.
- Thermostat suitable for cleaning with water (95°C).
 Rounded corners and a pivoting heating element with an intermediate stop position allow for easy cleaning.
- · «MELT» Position: melts solid fat without burning it.
- · High-quality components and finishes to meet the highest standards.
- \cdot Fully stainless steel, strong and durable
- · Adjustable height: 850-900 mm
- · Turbo option, ideal for frying frozen foods.
- Swiss Made: manufactured at our factory in Romanelsur-Morges.
- IPX4 Rating / 2-year warranty / 20-year availability of spare parts.

Options

- · Built-in installation
- · Turbo
- · Other voltages available on request

Accessories

- · Fine meshed basket
- · Microfilter with support
- One basket (350x285x135)
- · Fish grid
- · Draining rack

Certifications

· CB, UL

Technical drawings (mm)





