in ©

ralentine.ch

THE CORE 2200 TECHNICAL DATA SHEET



Technical data

Model / Type	CORE2200
Reference	8513
Tank	2x 7-8 litres
Dimensions*	400x600x850/900
Baskets [*]	158x285x135
Production capacity	46-54kg/h
Voltage	1N230V
Heating power	14.4 kW
Current	64A
Heating element	2
Temperature range	95°C – 190°C
Protection index	IPX4
Net weight	72kg
Power cable	2.5m
Remark	Supplied without plug













THE CORE 2200 TECHNICAL DATA SHEET



Features and benefits

- · Electromechanical thermostat
- · Temperature control knob
- · Integrated Sicotronic interface
- Intelligent adjustment for optimized performance and precise temperature control.
- · Maximum insulation to optimize efficiency and heat retention, with minimal energy loss.
- · Fry tank with a cold zone for waste collection below the heating element, slowing down oil degradation.
- Thermostat suitable for cleaning with water (95°C).
 Rounded corners and a pivoting heating element with an intermediate stop position allow for easy cleaning.
- · «MELT» Position: melts solid fat without burning it.
- High-quality components and finishes to meet the highest standards.
- · Fully stainless steel, strong and durable
- · Adjustable height: 850-900 mm
- \cdot Swiss Made: manufactured at our factory in Romanelsur-Morges.
- IPX4 Rating / 2-year warranty / 20-year availability of spare parts.

Options

- · Built-in installation
- · 2 Cables
- · Other voltages available on request

Accessories

- · Fine meshed basket
- · Microfilter with support
- · Fish grid
- · Draining rack

Certifications

· CB, UL

Technical drawings (mm)





