

TECHNICAL DATA SHEET

VMC-3 (T)



TECHNICAL DATA

Model / Type	VMC-3 / Built-in	VMC-3T / Built-in
Reference	8131-30 / 8131-30E	8137-30 / 8137-30E
Pan (litres)	25-40	
Dimensions (mm) Width Depth Height	350 600 850-900 / Built-in: 420	
Voltage	3N400V	
Kilowatts	6.6 kW	10 kW
Fuses	9.5A	14.5A
Heating element	1	
Temperature range	40°C – 105°C	
Protection index	IPX4	
Net weight (kg)	33	
Power cable (m)	2.5	
Remark	Without plug	

FEATURES AND BENEFITS

- 100% stainless steel construction, strong and sustainable.
- · GN 1/1 tank (310 x 510 x H300-310mm) for 25 to 40 litres, resistant to salted water, stamped in one piece.
- · Easy cleaning and optimum hygiene thanks to the rounded corners and the pivoting heating element.
- · Adjustable thermostat from 40°C to 105°C.
- · Water drain tap under the device.
- · Sold without baskets for the standard models (without lift). For baskets choice, refer to the "Accessories" section.
- · Security thermostat with reset button.
- Turbo option for higher performance.
- Large choice of accessories under the "Accessories" section.
- · Swiss Made: manufactured in our factory in Romanel-sur-Morges.
- IPX4 index / CB and DNV-GL certified / 2-year warranty / 20-year spare parts.

OPTIONS

- Automatic basket lifts (2x)
- Fresh water tap
- · Castors H850 or H900
- · Turbo
- · Built-in
- Marine
- · Other voltages on request

ACCESSORIES

- · Rectangular baskets
- · Round baskets
- · Small rectangular baskets (for portions)
- Perforated container GN1/1 x195 with handles
- Perforated container GN1/2 H195 with handles
- · Set of 6 numbered baskets for regeneration
- · Front draining shelf
- · Overflow pipe

CERTIFICATES

· CB, DNV-GL



DETAIL IMAGES

