

Webb Panel Fabric Detail (2025) Aspen

Natural brightness is rich in color.
Can be used in electric bonding process.
Ideal choice of office panel fabric.
High Abrasion Resistance.
Can be washed at 60°C. (140°F)
100% recycled polyester
Free of Hazardous Substances.
Pass BS7176 and CA117 flame retardant test
Passed and tested for UL1286 application (panel systems) E498710.

Composition:	100% Polyester
Weight:	215Grams per square meter. 366Grams per linear meter
Width:	170Cms / 67" +/-2%
Abrasion:	In excess of 30,000 Cycles {(ASTM D4966-12(2016) 12kPa Martindale & Pilling Tester}
Flammability:	BS EN 1021-1:1994 (Cigarette) BS EN 1021-2: 1994 (Match) BS 7176:1995 Low Hazard BS 476 Part 7 Class 1 California TB 117-2013 Section 1
Fastness to light:	4.5 (AATCC 16.3-2014) 40 Hours (AFU) Exposure
Fastness to rubbing:	Wet: 4.5 Dry: 4.5 (AATCC8-2016)
Maintenance & Cleaning:	N9NE Furniture recommends professional dry cleaning <ul style="list-style-type: none">• Protect from direct sunlight• Vacuum regularly using low suction• Wipe with a damp cloth using upholstery shampoo• Don't scrub or use stiff brush• Dry in the shade away from direct heat• Allow dry thoroughly before using
Color Matching:	Batch to batch variations in shade may occur within commercial tolerances. Samples cuttings from the current stock shades can be obtained on request.