

 **RODIN**<sup>®</sup>  
**CHROMA FLASH**<sup>™</sup>

*Consistent Flash Post-Curing Designed with Rodin<sup>®</sup> Materials*



Stable Material  
Performance



Predictable Surface  
and Aesthetic Outcomes



Open, Material-First  
System



Simplified, Low-Sensitivity  
Workflow

Engineered to deliver consistent, reliable polymerization without nitrogen, Chroma Flash simplifies post-curing while supporting predictable mechanical properties, surface quality, and workflow outcomes.



## Comparison Table

	Chroma Flash	Leading competitors
Xenon Flash Curing	✓	X
Integrated Material Library	✓	X
Customizable Save Profiles	✓	X
Tack Cure Cycles	✓	X
Seamless Workflow Intergration	✓	X
Wireless Connectivity	✓	X
N2 Compatibility	✓	X

## Technical Specifications

CATEGORY	SPECIFICATIONS
Inner Curing Chamber Dimension	111 x 111 x 43.5 mm
Device Dimensions	256 x 330 x 223.76 mm
Light / Source	Xenon Flash / Stroboscopic
Wavelength	280-950 nm
Rated Voltage	110-240V
Weight	8.2 kg
Open / Close System	Open
N <sub>2</sub> Compatibility	Yes



DESIGN



PRINT



MATERIALS



WASH & FINISH



CURE



DELIVER

