



MICRO OPTICAL FIBER DISTRIBUTION FRAME

Techlogiks micro ODF range is designed specifically for FTTH applications. Its compact size, light weight, high strength and impact resistance, integrated cables management makes it suitable for small fiber termination requirements.



Applications

- *Telecommunication Networks*
- *Local Area Networks*
- *FTTH*
- *CATV Networks*
- *Active Device Termination*

Features

- *Suitable for LC, SC adaptors.*
- *Up to 4 ports capacity.*
- *Compact size, light weight, Flame proof materials.*
- *Convenience and ease of handling*
- *Integrated heat shrink splice holder and fiber management*

Specifications

Specifications	
Dimensions	86mm (L) x 86mm (W) for 2 Port / 100mm (L) x 84mm (W) for 4 Port
Material	Flame retardant ABS
Color	Ivory/White
Splice Capacity	Max. 4 Fibers for 2 port / Max. 8 Fibers for 4 port
Adaptors	SC, SC/APC, LC, LC/APC

ORDERING INFORMATION

Part Number	Description
TL-FDF-MR02	Micro ODF Suitable for 2 SC Simplex adaptors
TL-FDF-MR04	Micro ODF Suitable for 2 LC Duplex adaptors
TL-FDF-MR04S08L	Micro ODF Suitable for 2 SC Simplex and 2 LC Duplex Snaggles Adapters