

Category 6A Unshielded Keystone Jack

Techlogiks Cat 6A Keystone Jack is designed to easily snap in and out of the wall outlet, patch panel and surface mount box. It is individually terminated using Insulation Displacement Connectors (IDC) with punch down tool for quick installation. Fully automatic press-fit production of PCB assembly to ensure consistency quality and complies with international standards up to 10GHz.



Applications

- 10GBASE-T, 1000BASE-T, 100BASE-Tx, 10BASE-T, 155M ATM,
- 4/16MB Token Ring, 100Mbps TP-PMD, ISDN, ADSL,
- Analog & Digital Voice (VoIP) / Video, Power over Ethernet, Control Signal.

Standards

- Lead-free & RoHS2 compliant.
- ANSI/TIA-568.2-D, ANSI/TIA-1096-A (FCC Part 68), ISO/IEC 11801 2nd edition and CENELEC EN 50173-1
- Level A reliability requirements of IEC 60603-7-2 and IEC 60603-7 for RJ45.
- Compatible for T568A AND T568B wiring schemes.

Specifications

Cap	High impact Polycarbonate (PC resin), UL 94 V-2 rated, transparent black
Housing	High impact Acrylonitrile Butadiene Styrene (ABS resin), UL 94 V-0 rated
Jack Contacts	5100W spring temper phosphor bronze, plated with hard gold over nickel under plate.
PCB	FR4, t=1.6mm, UL 94 V-0 rated
IDC Terminals	Phosphorous bronze plated with tin over nickel under plate.
IDC Block	High impact Polycarbonate (PC resin), UL 94 V-2 rated, RoHS 2 compliant.
Conductor Diameters	26 AWG – 22 AWG
Insulation Diameters	0.8mm – 1.0mm
Cable Diameters	5mm – 9mm

Electrical Characteristics

Voltage proof:	1000V DC or AC peak, contact-to-contact.
Current-carrying capacity:	0.75Amps minimum
Contact resistance:	20mohm maximum
Insulation resistance:	500Mohm minimum at 100V DC
Input to output resistance:	200mohm maximum
DC resistance:	0.2ohm maximum

Mechanical Characteristics

Mechanical operation	750 cycles min. for insertion / withdrawal with modular plug. 20 cycles min. for cable re-termination.
Effectiveness of connector coupling devices	50N (11lbf) for 60s ± 5s.

Environmental Characteristics

Temperature	-10°C ~ 60°C
Humidity	10% ~ 90%RH

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-JHC6AU-90	Cat 6A Unshielded Keystone Jack 90 Degree, White
TL-JHC6AU-180	Cat 6A Unshielded Keystone Jack 180 Degree, White
TL-JHC6AU-BL-90	Cat 6A Unshielded Keystone Jack 90 Degree, Black
TL-JHC6AU-BL-180	Cat 6A Unshielded Keystone Jack 180 Degree, Black