

### Fixed Shelf



#### Features

- *Materials: 1.2mm cool rolled steel.*
- *Color: black/gray.*
- *Surface finish: Degreasing, phosphoric, water cleaning, electro-static powder coating.*
- *Applications: setting hosts, monitor or other terminal/ ancillary equipment. Supporting 600,800,1000 width cabinets.*

#### ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-CAC-SHF-45	19" Fixed Shelf 450 mm depth
TL-CAC-SHF-60	19" Fixed Shelf 600 mm depth
TL-CAC-SHF-80	19" Fixed Shelf 800 mm depth
TL-CAC-SHF-10	19" Fixed Shelf 1000 mm depth

### Sliding Shelf



#### Features

- *Materials: 1.2mm cool rolled steel.*
- *Color: black/gray.*
- *Surface finish: Degreasing, phosphoric, water cleaning, electro-static powder coating.*
- *Applications: setting equipments requiring frequent operation Supporting 600,800,1000 width cabinets.*

#### ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-CAC-SHS-60	19" Sliding Shelf 600 mm depth
TL-CAC-SHS-80	19" Sliding Shelf 800 mm depth
TL-CAC-SHS-10	19" Sliding Shelf 1000 mm depth

### Keyboard Panel



#### Features

- *Materials: 1.2mm cool rolled steel.*
- *Rail: 12'/14' 2-section slide rail.*
- *Load bearing: 20kg.*
- *Color: black/gray.*
- *Surface finish: Degreasing, phosphoric, water cleaning, electro-static powder coating.*
- *Supporting 600,800,1000 width cabinets.*

#### ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-CAC-KP-60	19" Keyboard Panel

### Cantilever Shelf



#### Features

- *Materials: 1.2mm cool rolled steel.*
- *Color: black/gray.*
- *Surface finish: Degreasing, phosphoric, water cleaning, electro-static powder coating*
- *Applications: setting hosts, monitor or other terminal/ ancillary.*

#### ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-CAC-SHC-250	19" Cantilever Shelf 250 mm depth
TL-CAC-SHC-300	19" Cantilever Shelf 300 mm depth
TL-CAC-SHC-350	19" Cantilever Shelf 350 mm depth

### Blank Panel



#### Features

- *Materials: 1.2mm cool rolled steel.*
- *Color: black/gray.*
- *Surface finish: Degreasing, phosphoric, water cleaning, electro-static powder coating*
- *Applications: shielding equipment inside, dust-pro, and making cabinet looking neat.*

#### ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-CAC-BP-1	19" 1U Blank Panel
TL-CAC- BP-2	19" 2U Blank Panel
TL-CAC- BP-4	19" 4U Blank Panel

### Cooling Fan



#### Features

- *Specification: 220-240VAC, 50/60HZ, medium speed.*
- *Dimension: 120mm\*120mm\*38mm.*
- *Fame made by aluminum. Color: black.*
- *Air delivery: 195M3/H .*
- *Noise: <48dB.*
- *Working temperature: 0-70.*
- *Mounting position: horizontal mounting on the top of cabinet.*

#### ORDERING INFORMATION

PART NUMBER	DESCRIPTION
TL-CAC-CF-1	1 Cooling Fan
TL-CAC- CF-2	2 Cooling Fan
TL-CAC- CF-4	4 Cooling Fan

### Vertical Cable Manager



**Features**

- *Materials: 1.2mm cool rolled steel.*
- *Color: black/gray.*
- *Features: overall one-shot stamped; convenient for disassembling&mounting.*
- *Dimension: width: 60mm, depth: 95mm.*

ORDERING INFORMATION	
PART NUMBER	DESCRIPTION
TL-CAC-CMV	Vertical Cable Manager

### Horizontal Cable Manager - Ring Type



**Features**

- *Panel Frame: Carbon Steel, T=1.5mm, Powder Coating*
- *Metal Buckle: Carbon Steel, T=2.0mm, Powder Coating*
- *Color: Black*
- *Burr: 0.05mm Max*
- *Dimension: Height - 1U, Width - 19", Depth - 60mm*

ORDERING INFORMATION	
PART NUMBER	DESCRIPTION
TL-CAC-CMRG-1	1U Cable Manager Ring Type

### Horizontal Cable Manager - Box Type



**Features**

- *Cover Material: Carbon Steel, T=1.0mm, Powder Coating*
- *Bottom Material: Black*
- *Color: Black*
- *Burr: 0.05mm Max*
- *Dimension: Height- 1U, Width - 19", Depth - 70mm*

ORDERING INFORMATION	
PART NUMBER	DESCRIPTION
TL-CAC-CMBX-1	1U Cable Manager Box Type

### Horizontal Cable Manager - Brush Type



**Features**

- Panel Frame: Carbon Steel, T=1.5mm, Powder Coating
- Color: Black
- Burr: 0.05mm Max
- Dimension: Height - 1U, Width - 19"

**ORDERING INFORMATION**

PART NUMBER	DESCRIPTION
TL-CAC-CMBR-1	1U Cable Manager Brush Type

### Castors



**Features**

- Load holding: 150kg/pcs, 240kg/pcs.
- Wheel made from good quality nylon compound.
- Features: free rotating, heavy loading.
- Mounting position: on the bottom of cabinet.
- Applications: moving cabinet easily to any direction.

**ORDERING INFORMATION**

PART NUMBER	DESCRIPTION
TL-CAC-CST	Heavy Duty Castors

### Screws and Nuts



**Features**

- Nuts: M6 spring square nuts.
- Screw: M6\*12 screw.
- Surface finish: zinc coating.
- Applications: fixing cabinet and 19' EIA standard equipment.

**ORDERING INFORMATION**

PART NUMBER	DESCRIPTION
TL-CAC-SN	Square Nut and Screws

CABINET ACCESSORIES

**Lock**



**Features**

- Name: cabinet lock.
- Specifications: round lock (optional).
- Surface treatment: spray.
- Characteristics: the key to universal.
- Mounting position: the cabinet front door, back door and side door.

**ORDERING INFORMATION**

PART NUMBER	DESCRIPTION
TL-CAC-LK	Cabinet Lock

**Digital Temperature Unit**



**Features**

- Power supply: 85-265VAC.
- Sensor: International cu50 resistance.
- Measuring range: -20—80.
- Measurement accuracy: 1.0(+/-1.0%).
- Sampling rate: 2/second.
- Output form: double relays(one group for master control, another one for alarm).
- Sensor's differential gap adjustable.
- Sensor support open circuit alarm.
- Power consumption: <5W.
- Ambient temperature: -10-50

**ORDERING INFORMATION**

PART NUMBER	DESCRIPTION
TL-CAC-DTU	Digital Temperature Unit

**Power Distribution Unit**



**Features**

- Rating Voltage: 250VAC 50/60Hz
- Socket Quantity: 6 Way, 10 Way
- Rating Current: 13 Amps
- Max. Power: 3250W
- Socket and Plug : UK Type
- Mounting Type : 6 Way - Horizontal, 10 Way - Vertical
- 19" Rack mountable 6 way PDU
- CE Approved : Yes
- Surge Protection: No
- RoHS : Yes
- Industrial PDU's are also available

**ORDERING INFORMATION**

PART NUMBER	DESCRIPTION
TL-CAC-PDU6	6 Way PDU, 1U, 2 Meter Cable
TL-CAC-PDU10	10 Way PDU, 1U, 2 Meter Cable

## 13Amp UK Plug Universal Type Power Distribution Unit – 06 Way



**BS1363 13A Plug**

### Specifications

Item	Detailed Description
Socket Type	GB2099.3 Socket [6];
Socket Quantity	6
Power Input	Left-end single input
Bracket Install	Frontal installation
Cable with plug	BS1363 13A plug
Control Function	Red switch (One Number)
Protection Function	No protecting function
Case	Black
Cable Specification	3 x 1.5 mm <sup>2</sup> x 1.8M
Product Size	L x W x H = 486.7 x 44.4 x 44.4 mm
Mounting Length	465.7 mm
Case Length	433.7 mm



PDU Exponent	1.069
Fittings	4pcs Bolt
Rating Voltage	250VAC
Rating Current	13A
Max. Power	3250W
Safety Authentication	UK RoHS CA
Socket assemble	No
Interior Connection Wire	1.5 mm <sup>2</sup> (16AWG)
Interior Connection Style	Standard connection

**Ordering Information**

<b>Part Number</b>	<b>Description</b>
TL-CAC-PDU6-UNI	06 Way, 13Amp UK Plug, Universal Type Power Distribution Unit, 1.8 Meter Cable Length

POWER DISTRIBUTION UNIT

## 16Amp Industrial Type Power Distribution Unit – 12 Way



IEC60309 plug (16A 2P+E)

POWER DISTRIBUTION UNIT

Specification	
Item	Detailed Description
Socket Type	BS1363(90degree) Outlet Module [12];
Socket Quantity	12 way
Power Input	Left end single input
Bracket Install	Inverse installation
Cable with plug	IEC60309 plug (16A 2P+E)
Control Function	No controlling function
Protection Function	No protecting function
Case	Black



Cable Specification	3 x 2.5 mm <sup>2</sup> x 3M
Product Size	L x W x H = 770 x 44.4 x 56 mm
Mounting Length	745 mm
Case Length	720 mm
PDU Exponent	1.709
Fittings	2pcs $\phi$ 6x16mm cross bolt, 2pcs M6 float nut, PDU manual
Rating Voltage	250VAC 50/60Hz
Rating Current	16A
Max. Power	4000W
Safety Authentication	CE, RoHS
Interior Connection Wire	1.5 mm <sup>2</sup>
Interior Connection Style	Group connection
Fix the Cable	Small cable clamp

**Ordering Information**

<b>Part Number</b>	<b>Description</b>
TL-CAC-PDU12-16A-IND	12 Way, 16Amp, Industrial Type Power Distribution Unit, 3.0mtr cable length

POWER DISTRIBUTION UNIT

### 32Amp Industrial Type Power Distribution Unit – 12 Way



IEC60309 plug (32A 2P+E)

POWER DISTRIBUTION UNIT

Specification	
Item	Detailed Description
Socket Type	BS1363(90degree) Outlet Module [12];
Socket Quantity	12 way
Power Input	Left end single input
Bracket Install	Inverse installation
Cable with plug	IEC60309 plug (32A 2P+E)
Control Function	No controlling function
Protection Function	No protecting function
Case	Black



Cable Specification	3 x 2.5 mm <sup>2</sup> x 3M
Product Size	L x W x H = 795 x 44.4 x 56 mm
Mounting Length	770 mm
Case Length	745 mm
PDU Exponent	1.709
Fittings	2pcs $\phi$ 6x16mm cross bolt, 2pcs M6 float nut, PDU manual
Rating voltage	250VAC 50/60Hz
Rating Current	32A
Max. Power	8000W
Safety Authentication	CE, RoHS
Interior Connection Wire	2.5 mm <sup>2</sup>
Interior Connection Style	Group connection
Fix the Cable	Cable clamp

**Ordering Information**

<b>Part Number</b>	<b>Description</b>
TL-CAC-PDU12-32A-IND	12 Way, 32Amp, Industrial Type Power Distribution Unit, 3.0mtr cable length

POWER DISTRIBUTION UNIT