

Aggregation Switch

HSP-IO-24S4XS-C3A +

24-Port SFP L3 Managed Switch



Overview

- Fully Managed L3 Switch with wire speed Non-Blocking Architecture
- All Gigabit Ethernet Access Ports with 10G Uplinks in a fixed 1U configuration
- 24x100/1000M SFP Gigabit Access Ports with 4x100/1000M RJ45 Combo Ports
- 4x1/10G SFP+ Uplink Ports that allow termination on either fiber or copper based on SFP module
- Powerful WebGUI with DMS and automapping feature
- Upto 128 Gbps Switching capacity and up to 95.232 MPPS of Full Duplex Throughput
- Comply with Energy Efficient Ethernet Standards (802.3az)
- Suitable as access or aggregation switch in Enterprise/ Campus/ Telco Environment

Switch Ports

- 24x100/1000M SFP Gigabit Access Ports with 4x100/1000M RJ45 Combo Ports
- 4x1/10G SFP+ Uplink Ports (MSA Compliant) with the flexibility to terminate the connection on copper or fiber-based SFP module
- One Serial Console Port and One Out-of-Band Management Port
- Link / Speed / LED Status on All ports
- System status LED and onboard RESET button

Industry Standard Management with Automation

- **Management Interfaces:** CLI and WebGUI (HTTP and HTTPS)
- **Virtual Stack:** Single IP Management
- **Protocol Support:** Dual Stack (IPv4/IPv6), Telnet, SSHv2, Syslog, SNMP v1/v2/v3, SMTP
- **Monitoring & Analytics:** RMON, sFlow, TWAMP Light, Port & VLAN Mirroring, L2 and L3 Traceroute
- **Time Services:** NTP and Secure NTP
- **IP Services:** DHCP Server, Relay, and Client
- **File Transfer & Provisioning:** TFTP, SCP, SFTP, Zero Touch Provisioning
- **Diagnostics & Resiliency:** Time Domain Reflectometry, Dying Gasp

HSP-IO-24S4XS-C3A +

KEY FEATURE HIGHLIGHTS



Rich L2 Features

- **VLANs:** Support up to 4094 VLAN IDs, Voice VLAN, IP-subnet VLAN, Protocol-based VLAN, Private VLAN, MAC-based VLAN, GVRP/MVRP for dynamic VLAN registration
- **Loop Avoidance & Resiliency:** STP (802.1D), RSTP (802.1w), MSTP (802.1s); STP Root and Edge Port Protection; ERPS (ITU-T G.8032); UDLD (Unidirectional Link Detection); IEEE 802.3x Flow Control
- **Multicast:** IGMP v1/v2/v3 Snooping, IGMP Filtering, IGMP Proxy, IGMP Querier, MLD Snooping and MVR (Multicast VLAN Registration)
- LACP-based LAG, Static LAG with load sharing and active-passive policies
- IEEE 802.1Q VLAN Tagging, QinQ (Port-based)
- **QoS:** Up to eight priority queues, Rate Limiting/Policing, Shaping (SP, WRR), Multi-Field (802.1p/DSCP) Classification and Remarking
- LLDP and LLDP-MED for end-point/VoIP device discovery
- **MAC Table:** 32K entries, Jumbo MTU: 10240 Bytes

L3 Features

- IPv4 and IPv6 Static Routing
- RIP v1/v2 L3 Dynamic Routing
- OSPFv2/v3 L3 Dynamic Routing
- Inter-VLAN Routing
- IPv4/IPv6 Dual Stack

Advanced Features

- IEEE 802.3ah Link-level OAM
- IEEE 802.1ag Ethernet CFM (ITU-T Y.1731 Performance Monitoring)

Security Features

- Up to 2000 L2/L3/L4 ACL with extended features, Time-based ACLs
- 802.1X Port Security with RADIUS Accounting & Dynamic VLAN Assignment, Dynamic/Downloadable ACLs
- **AAA Support:** TACACS+, RADIUS and RADSec
- DHCP snooping, Dynamic ARP Inspection, DHCPv6 Guard
- Inherent DoS Prevention, Port Security, Sticky MAC, IP-MAC Binding
- PKI Key, Certificate, SSL IPv4/IPv6, IPv6 Source Guard
- Storm Control - Broadcast, Multicast and Unknown Unicast

Switching / Forwarding Capacity

Switching Capacity	128 Gbps
Forwarding Capacity	95.232 MPPS

Design Parameters

- Memory (DRAM): 2GB and Storage (Flash): 4GB
- Packet Buffer: 6MB
- Operating Temperature: -5°C to 55°C (5% to 95% non-condensing)
- Altitude: 3000 Meters (10,000 Feet)
- Dimension (WxHxD): 442 x 44 x 211 mm

Power Supply Options

- Integrated Single AC Power (100-240 VAC 50-60 Hz)
- Integrated Redundant Dual AC Power (100-240 VAC 50-60 Hz)
- Modular Single AC Power (100-240 VAC 50-60 Hz)
- Modular Redundant Dual AC Power (100-240 VAC 50-60 Hz)

HSP-IO-24S4XS-C3A +

KEY FEATURE HIGHLIGHTS



Compliance & Certifications

EMI/EMC (TEC)	IEC 61000-4
EMI/EMC (CE)	EN55032 / EN55024
FCC Compliance	FCC Part-B
Safety (CE)	EN62368-1
Reliability Test	QM333 Cyclic
Environmental Tests	IEC 60068-2
ESS Tests	IEC 60068-2 (Vibration, Shock, Drop, Bump, High Altitude)
MTCTE (India)	Mandatory Testing & Certification of Telecom Equipment
Trusted Portal	Country-specific security/trust compliance
RoHS	Restriction of Hazardous Substances
IPv6 Logo	IPv6 Ready Logo Certification (Phase-2 Gold)

Ordering Information

Model No.	Description
HSP-IO-24S4XS-C3A +	IO, 24-Port SFP, L3 Managed Switch, 4x1/10G SFP+ Uplinks with AC power supply
HSP-IO-PSA-SI	Integrated Single AC Power Supply
HSP-IO-PSA-DI	Integrated Redundant Dual AC Power Supplies
HSP-IO-PSA-SM	Modular Single AC Power Supply
HSP-IO-PSA-DM	Modular Redundant Dual AC Power Supplies
HSP-IO-Cable-AC-IN	AC Power Cable, 1.5M (India Plug)

Disclaimer: HFCL, IO by HFCL, and their respective logos are trademarks and/or registered trademarks of HFCL Limited. HFCL Limited assumes no responsibility for any inaccuracies in this document and reserves the right to revise or transfer this document without notice. All other trademarks, service marks, registered marks, or registered service marks mentioned herein are the property of their respective owners.

Last Updated April 2026



Email: iosupport@hfcl.com
Website: hfcl.com | io.hfcl.com
Office: 8, Commercial Complex, Masjid Moth, Greater Kailash II, New Delhi 110048