

Industrial Access Switch

HSP-IO-8GE2S-I2PDH+

8-Port PoE+ L2 Managed Switch



Overview

- Temperature hardened fully Managed L2 Switch with wire speed Non-Blocking Architecture
- All Gigabit Ethernet Access Ports with 2x1G SFP Uplinks in a DIN rail mounting configuration
- 8x10/100/1000 Base-T PoE/PoE+ Access Ports with auto MDI-MDIX and auto negotiation support
- 2x1G SFP Uplink Ports that allow termination on either fiber or copper based on SFP module
- Powerful WebGUI with industry standard Command Line Interface
- Upto 20 Gbps Switching capacity and up to 14.88 MPPS of Full Duplex Throughput
- Comply with Energy Efficient Ethernet Standards (802.3az)
- Suitable for temperature hardened environment and deployment of Wi-Fi AP/CCTV/IP Phones

Switch Ports

- 8x10/100/1000 Base-T PoE+ Gigabit Access Ports
- 2x1G SFP Uplink Ports (MSA Compliant)
- One Serial Console Port and One Out-of-Band Management Port
- Digital Input and Digital Output Relay for SCADA Applications
- DIP Switch for Rapid Ring Settings
- Link, Speed, Alarm, RM/RC and Power Status LEDs
- System status LED & onboard RESET button

Industry Standard Management with Automation

- **Management Interfaces:** CLI and WebGUI (HTTP and HTTPS)
- **Protocol Support:** Dual Stack (IPv4/IPv6), Telnet, SSHv2, Syslog, SNMP v1/v2/v3, SMTP
- **Monitoring & Analytics:** RMON, sFlow, TWAMP Light, Port & VLAN Mirroring, L2 and L3 Traceroute
- **Time Services:** NTP and Secure NTP
- **IP Services:** DHCP Server, Relay, and Client
- **File Transfer & Provisioning:** TFTP, SCP, SFTP, Zero Touch Provisioning
- **Diagnostics & Resiliency:** Time Domain Reflectometry, Dying Gasp

HSP-IO-8GE2S-I2PDH+

KEY FEATURE HIGHLIGHTS



Rich L2 Features

- **VLANs:** Support up to 4094 VLAN IDs, Voice VLAN, IP-subnet VLAN, Protocol-based VLAN, Private VLAN, MAC-based VLAN, GVRP/MVRP for dynamic VLAN registration
- **Loop Avoidance & Resiliency:** STP (802.1D), RSTP (802.1w), MSTP (802.1s); STP Root and Edge Port Protection; ERPS (ITU-T G.8032); UDLD (Unidirectional Link Detection); IEEE 802.3x Flow Control
- **Multicast:** IGMP v1/v2/v3 Snooping, IGMP Filtering, IGMP Proxy, IGMP Querier, MLD Snooping and MVR (Multicast VLAN Registration)
- LACP-based LAG, Static LAG with load sharing and active-passive policies
- IEEE 802.1Q VLAN Tagging, QinQ (Port-based)
- **QoS:** Up to eight priority queues, Rate Limiting/Policing, Shaping (SP, WRR), Multi-Field (802.1p/DSCP) Classification and Remarking
- LLDP and LLDP-MED for end-point/VoIP device discovery
- **MAC Table:** 8K entries, Jumbo MTU: 9216 Bytes

PoE Features

- PoE Budget - 240W
- Per port PoE configuration and scheduling
- Auto PoE Check and reboot if device does not respond
- Persistent PoE and Power Delay (to let the device boot)

Security Features

- L2/L3/L4 ACL with extended features, Time-based ACLs
- 802.1X Port Security with RADIUS Accounting & Dynamic VLAN Assignment, Dynamic/Downloadable ACLs
- **AAA Support:** TACACS+, RADIUS and RADSec
- DHCP snooping, Dynamic ARP Inspection, DHCPv6 Guard
- Inherent DoS Prevention, Port Security, Sticky MAC, IP-MAC Binding
- PKI Key, Certificate, SSL IPv4/IPv6, IPv6 Source Guard
- Storm Control - Broadcast, Multicast and Unknown Unicast

Advanced Features

- IEEE 802.3ah Link-level OAM
- IEEE 802.1ag Ethernet CFM (ITU-T Y.1731 Performance Monitoring)
- IEEE 1588 v2 PTP (Precision Time Protocol)

Switching / Forwarding Capacity

Switching Capacity	20 Gbps
Forwarding Capacity	14.88 MPPS

Design Parameters

- Operating Temperature: -40°C to 75°C
- DIN rail mountable
- Humidity: 5% to 95% non-condensing
- Altitude: 3000 Meters (10,000 Feet)
- Dimension (WxHxD): 62 x 135 x 130 mm

Power Supply Options

- Integrated Dual DC Power Supply (54W)

HSP-IO-8GE2S-I2PDH+

KEY FEATURE HIGHLIGHTS



Compliance & Certifications

EMI/EMC (TEC)	IEC 61000-4
EMI/EMC (CE)	EN55032 / EN55024
FCC Compliance	FCC Part-B
Safety (CE)	EN62368-1
Reliability Test	QM333 Cyclic
Environmental Tests	IEC 60068-2
ESS Tests	IEC 60068-2 (Vibration, Shock, Drop, Bump, High Altitude)
Ingress Protection	IP50
MTCTE (India)	Mandatory Testing & Certification of Telecom Equipment
Trusted Portal	Country-specific security/trust compliance
RoHS	Restriction of Hazardous Substances
IPv6 Logo	IPv6 Ready Logo Certification (Phase-2 Gold)

Ordering Information

Model No.	Description
HSP-IO-8GE2S-I2PDH+	IO, 8-Port, PoE+, L2 Managed Industrial Switch, 2x1G SFP Uplinks, Dual DC Power Supplies

Disclaimer: HFCL, IO by HFCL, and their respective logos are trademarks and/or registered trademarks of HFCL Limited. HFCL Limited assumes no responsibility for any inaccuracies in this document and reserves the right to revise or transfer this document without notice. All other trademarks, service marks, registered marks, or registered service marks mentioned herein are the property of their respective owners.

Last Updated April 2026



Email: iosupport@hfcl.com
Website: hfcl.com | io.hfcl.com
Office: 8, Commercial Complex, Masjid Moth, Greater Kailash II, New Delhi 110048