DATASHEET

IO-SFP-CF-GS-ER

IO, 1G Optical Extended Range SFP



Description

The IO-SFP-CF-GS-ER is a single mode SFP transceiver designed for Gigabit Ethernet and 1G Fiber Channel applications. It uses a 1550nm DFB laser transmitter and a PIN photodiode receiver and supports transmission distances up to 40km on standard single mode fiber.

The module supports data rates up to 1.25Gbps and complies with the SFP Multi-Source Agreement and the Digital Diagnostics Monitoring as per SFF-8472. The diagnostics interface provides real time monitoring of temperature, supply voltage, transmit optical power, receive optical power and bias current.

The transceiver uses a single 3.3V power supply and is available in Commercial 0°C to +70°C operating temperature option. It is suitable for long reach Gigabit Ethernet links, Fiber Channel networks and 40km point to point optical systems.

Key Specifications

- 1G SFP transceiver with duplex LC connector
- 1550nm DFB transmitter and PIN photodiode receiver
- Supports 1.25Gbps Ethernet and 1.063Gbps Fiber Channel
- Up to 40km transmission distance over single mode fiber
- Typical power consumption around 1W
- Temp operating conditions: Commercial 0°C to +70°C

© 2026 HFCL Limited, All rights reserved.

IO-SFP-CF-GS-ER

IO, 1G Optical Extended Range SFP



Technical Data

Parameter	Value	Parameter	Value
Form Factor	SFP	**Transmitter Data**	
Transmission Media	SM (LC)	Tx Power	-5 to 0dBm[1)]
Typical Reach	40km	Tx Wavelength	1530-1570nm
Nominal Wavelength	1550nm	Extinction Ratio	≥ 9dB
Data Rate Support	10Mbps to 1.25Gbps	**Receiver Data**	
Protocol Support	GbE, 1G FC	Rx Sensitivity	-23dBm[1) 2)]
Power Consumption	<1.0W	Rx Overload, Max	-1dBm[2)]
Operating Temperature	0°C to 70°C	Rx Wavelength	1260 -1610nm
Storage Temperature	-40°C to 85°C	LOS Assert	-38dBm
DDM	Yes	LOS De-assert	-24dBm
		LOS Hysteresis	0.5dB

1. Average Power
2. @1250 Mbps, BER ≤1×10^{-12}, PRBS 2^7-1

© 2026 HFCL Limited, All rights reserved.

IO-SFP-CF-GS-ER

IO, 1G Optical Extended Range SFP



Safety/Regulatory Compliance

- Class 1 laser safe
- RoHS Compliance

Absolute Maximum Rating

Parameter	Value
Supply Voltage	-0.5V to 3.75V
Storage Temperature	-40°C to 85°C
Relative Humidity	85%
Max Rx Optical Power	-1dBm

Ordering Information

Model No.	Description
IO-SFP-CF-GS-ER	IO, 1G Optical Extended Range SFP Commercial Grade

Disclaimer: HFCL, IO by HFCL, and their respective logos are trademarks and/or registered trademarks of HFCL Limited. HFCL Limited assumes no responsibility for any inaccuracies in this document and reserves the right to revise or transfer this document without notice. All other trademarks, service marks, registered marks, or registered service marks mentioned herein are the property of their respective owners.

Last Updated 16 July 2026

Email: iosupport@hfcl.com
Website: hfcl.com | io.hfcl.com
Office: 8, Commercial Complex, Masjid Moth, Greater Kailash II, New Delhi 110048

© 2026 HFCL Limited, All rights reserved.